



nShield Security World

CodeSafe 5 v13.6.12 Developer Guide

22 August 2025

Table of Contents

1. Introduction	1
2. Overview of CodeSafe 5	2
2.1. Applications as container images	2
2.2. Easy and fast network connectivity	2
2.3. 'Secure by default' client communication	2
2.4. Better language support	3
2.5. Developer authentication	3
3. Install the CodeSafe 5 SDK on Linux	4
4. Install the CodeSafe 5 SDK on Windows	5
4.1. Prerequisites	5
4.2. Install the Security World Software	5
4.3. Install CodeSafe 5	5
5. nShield 5c Codesafe 5 Configuration	6
6. Build CodeSafe 5 SDK apps	7
6.1. General SDK use	7
6.2. Prerequisites	7
6.3. SDK file structure overview	7
6.3.1. SDK location	7
6.3.2. Container root file system	7
6.3.3. CMake	8
6.3.4. Include directories	8
6.3.5. SEE specific libraries	9
6.3.6. Compatibility	9
6.4. Building new SEE machines with SEELib	9
6.4.1. Developer authentication	9
6.4.2. Deploying SEE machines	10
6.4.3. SEE machine initialization requirements	10
6.4.4. SEELib Functions	10
6.4.5. Host/SEE machine communication	12
6.5. Compatibility layer for legacy SEE machines	12
6.5.1. Module-side compatibility layer	13
6.5.2. Host-side compatibility layer	14
6.5.3. Initialize module-side compatibility	14
6.5.4. Use module-side compatibility	14
6.5.5. Initialize host-side application compatibility	15
6.5.6. Use host-side application compatibility	15
7. Sign and deploy CodeSafe 5 SDK apps using csadmin	18

7.1. Signing CodeSafe images	18
7.2. The csadmin utility tool.....	19
7.2.1. Generate loadable images.....	19
7.2.2. Sign images.....	22
7.2.3. Create a developer ID certificate	24
7.3. Example CodeSafe developer process.....	24
7.3.1. Create developer ID keys	24
7.3.2. Load your certificate	26
8. Build and sign example SEE machines on Linux	28
8.1. Build module-side C examples.....	28
8.2. Building Host Side C Examples.....	28
8.3. Build CS5 Images for Python Examples	29
8.4. Sign CodeSafe Images	29
8.5. Run NetSEE examples	30
8.5.1. helloworld_tcp.....	31
8.5.2. helloworld_udp	32
8.6. Run NetSEE examples via SSH tunnel	34
8.6.1. helloworld_tcp via SSH Tunnel.....	34
8.7. Run CSEE examples via SSH tunnel	38
8.7.1. hello CSEE via automatic configuration	38
8.7.2. tickets CSEE via automatic configuration	39
8.7.3. benchmark CSEE via automatic configuration	41
9. Build and sign example SEE machines on Windows	43
9.1. Prerequisites.....	43
9.2. Building Windows CodeSafe C, CSEE, and NETSEE examples	43
9.2.1. Host-side examples	44
9.2.2. Module-side examples	44
9.3. CS5 images for Python examples	44
9.4. Sign CodeSafe images.....	45
10. Build and run Java examples	48
10.1. Prerequisites	48
10.2. The Java interface.....	48
10.3. Build the examples.....	49
10.4. Run the examples	49
10.4.1. BenchMark5	50
10.4.2. Echo5	51
10.4.3. HelloWorld5	52
10.4.4. HostTickets5	53
11. Debug CodeSafe 5 SEE machines	54

11.1. SEE machine logging	54
11.1.1. config log set enabled	54
11.1.2. config log set disabled	54
11.1.3. log get	55
11.1.4. log clear	55
11.2. Crash Reporter	55
12. Uninstall the CodeSafe 5 SDK	57
13. Port existing CodeSafe application to CodeSafe 5	58
13.1. Communication with the host	58
13.2. SEELib library	59
13.3. Deployment differences	59
13.4. User Data	60
14. Supporting legacy CodeSafe Direct	61
14.1. Legacy CodeSafe Direct	61
14.2. CodeSafe 5	61
15. SEE API documentation	62
15.1. SEELib functions	62
15.1.1. SEELib_init	62
15.1.2. SEELib_ReadUserData	62
15.1.3. SEELib_ReleaseUserData	62
15.1.4. SEELib_InitComplete	63
15.1.5. SEELib_StartTransactListener	63
15.1.6. SEELib_Transact	63
15.1.7. SEELib_MarshalSendCommand	63
15.1.8. SEELib_GetUnmarshalResponse	64
15.1.9. SEELib_FreeCommand	64
15.1.10. SEELib_FreeReply	64
15.1.11. SEELib_SetPort	64
15.1.12. SEELib_SubmitCoreJob	65
15.1.13. SEELib_GetCoreJob	65
15.1.14. SEELib_GetUserDataLen	65
15.1.15. SEELib_Submit	66
15.1.16. SEELib_Query	66
15.1.17. SEELib_AwaitJob	66
15.1.18. SEELib_AwaitJobEx	67
15.1.19. SEELib_ReturnJob	67
15.1.20. SEELib_StartProcessorThreads	68
15.1.21. SEELib_StartSEETaskListener	68
15.1.22. SEELib_QuerySEETask	69

15.1.23. SEELib_ReleaseSEETask	69
15.2. Host-side SEETasks	69
16. System calls allowed by CodeSafe 5 SEE machines	71

1. Introduction

CodeSafe is a runtime on the Entrust nShield HSM that allows third-party developers to run their own code within the secure boundary of the module. Using the CodeSafe Developer Kit, developers write their own CodeSafe Apps, cross-compile them and package them to run on the HSM. While on the HSM, the CodeSafe App is segregated from the actual keys loaded onto the module, including the keys the App uses. This means that CodeSafe can be used without affecting the FIPS 140 validation of the module it runs on.

Where the HSMs provide security controls on key usage, CodeSafe provides control over application code. Depending on the runtime used, you are either sending nCore commands to the HSM, or designing your own protocol to send data and commands back and forth.

The CodeSafe Developer Kit includes the Secure Execution Engine (SEE) technology. The CodeSafe product comprises a suite of cross-compilers and support tools that allow you to develop SEE machines.

With CodeSafe, you can build and deploy Trusted Agents to perform application-specific security functions on your behalf on unattended servers, or in unprotected environments where the operation of the system is outside of your direct control. Examples of Trusted Agents include digital meters, authentication agents, timestamp servers, audit loggers, digital signature agents and custom encryption processes.

Traditionally, HSMs have protected cryptographic keys within a defined security boundary; SEE allows you to extend that security boundary to include code that utilizes those protected keys. The code itself is signed to provide additional protection.

2. Overview of CodeSafe 5

2.1. Applications as container images

In CodeSafe 5, the application is a container image, meaning a complete filesystem image that can contain multiple executables, libraries, scripts, and data files.

This has the following benefits:

- Data files can be written to the local filesystem and persisted over container shutdown and restart.
- The application can comprise multiple co-operating processes. This can enhance security by separating memory spaces and reliability by allowing individual processes to be restarted if they crash or leak memory.
- Third-party or pre-existing source code that works on Linux can be built and run without modification.
- Standalone tools can be executed as subprocesses.
- Dynamically-loaded libraries work in a regular way. Code architectures that make use of plug-in modules make code development easier and reduce the attack surface by excluding unwanted code.

2.2. Easy and fast network connectivity

nShield 5 HSMs and CodeSafe 5 containers are logically connected via TCP and UDP networking. The container running the SEE Machine can receive incoming connections from the host side app, establishing two-way communication between host side app and SEE machine. Existing software that makes use of incoming or outgoing network connections can run with little or no modifications.

Kernel-implemented networking provides good performance both for throughput and for latency compared to previous HSM models.

2.3. 'Secure by default' client communication

The CodeSafe 5 execution environment includes both a configurable firewall and an SSH server. The firewall is set according to configuration in the signed CodeSafe 5 application package so that only the network ports required by the application are allowed. The CodeSafe SSH server also allows a secure tunnel to be configured to the CodeSafe 5 application to encapsulate a plaintext TCP protocol within a secure layer. The client credentials required

to access this tunnel can be configured using the support tools, or (when using CSEE) can be configured automatically by the nShield software.

This means that applications, including applications ported from older CodeSafe SEE machines, can benefit from strong authentication of their clients and protection from unauthorized network traffic without additional code.

2.4. Better language support

The CodeSafe 5 SDK supports:

- C and C++
- Python

The `nfpython` module provides easy access to nCore API commands.

The container environment has a regular Linux filesystem and supports system calls for network and file I/O, so a wide range of standard and third-party Python modules can be used without modification.

Refer to the nShield Security World Release Notes for information about the supported version for this release.

CodeSafe applications can be written using mixed languages with the usual range of IPC and calling mechanisms available to the developer.

2.5. Developer authentication

CodeSafe 5 uses Entrust X.509 certificates to link the CodeSafe application to a real-world developer identity through code signing.

This allows the administrator of an HSM to, for example, restrict the HSM to authorized in-house applications or to those provided by trusted development partners.

3. Install the CodeSafe 5 SDK on Linux

1. Make sure that the following nShield ISO images are available locally:

- `SecWorld_Lin64-13.x.y.iso`
- `Codesafe_Lin64-13.x.y.iso`

Where `<x.y>` are the same versions for Security World and CodeSafe.

2. Create a mount directory for each ISO:

```
mkdir ~/secworld_iso_mountpoint
mkdir ~/codesafe_iso_mountpoint
```

3. Mount the ISO images to their respective directories:

```
sudo mount <PATH_TO>/SecWorld_Lin64-13.x.y.iso ~/secworld_iso_mountpoint/
sudo mount <PATH_TO>/Codesafe_Lin64-13.x.y.iso ~/codesafe_iso_mountpoint/
```

The nShield CodeSafe 5 hostside is located in tarballs under:

```
ls ~/codesafe_iso_mountpoint/linux/amd64/
csdref.tar.gz  csd.tar.gz
```

The nShield Security World hostside is located in tarballs under:

```
ls ~/secworld_iso_mountpoint/linux/amd64/
ctd.tar.gz  devref.tar.gz  javasp.tar.gz  ncsnmp.tar.gz
ctls.tar.gz  hwsp.tar.gz  jd.tar.gz  raserv.tar.gz
```

4. Untar the tarballs into the root directory:

```
tar -zxvf ~/codesafe_iso_mountpoint/linux/amd64/csd.tar.gz -C /
tar -zxvf ~/codesafe_iso_mountpoint/linux/amd64/csdref.tar.gz -C /
tar -zxvf ~/secworld_iso_mountpoint/linux/amd64/ctd.tar.gz -C /
tar -zxvf ~/secworld_iso_mountpoint/linux/amd64/devref.tar.gz -C /
tar -zxvf ~/secworld_iso_mountpoint/linux/amd64/javasp.tar.gz -C /
tar -zxvf ~/secworld_iso_mountpoint/linux/amd64/ncsnmp.tar.gz -C /
tar -zxvf ~/secworld_iso_mountpoint/linux/amd64/ctls.tar.gz -C /
tar -zxvf ~/secworld_iso_mountpoint/linux/amd64/hwsp.tar.gz -C /
tar -zxvf ~/secworld_iso_mountpoint/linux/amd64/jd.tar.gz -C /
tar -zxvf ~/secworld_iso_mountpoint/linux/amd64/raserv.tar.gz -C /
```

This installs the nShield CodeSafe 5 SDK to `/opt/nfast/c/csd5` and the nShield CodeSafe 5 SDK Python files to `/opt/nfast/python3/csd5`.

4. Install the CodeSafe 5 SDK on Windows

4.1. Prerequisites

Make sure that the following nShield ISO images are available locally:

- `SecWorld_Windows-13.x.y.iso`
- `Codesafe_Windows-13.x.y.iso`

Where `<x.y>` are the same versions for Security World and CodeSafe.

4.2. Install the Security World Software

1. Log in as Administrator or as a user with local administrator rights.
2. Mount the Security World Software ISO image and navigate into the mounted directory.
3. Launch `setup.msi`.
4. Follow the on-screen instructions.
5. Accept the license terms and select **Next** to continue.
6. Specify the installation directory and select **Next** to continue.
7. Select **Install**.
8. Select **Finish** to complete the installation.

4.3. Install CodeSafe 5

1. Mount the CodeSafe 5 SDK ISO image and navigate into the mounted directory.
2. Launch `setup.msi`.
3. Follow the on-screen instructions.
4. Accept the license terms and select **Next** to continue.
5. Specify the installation directory and select **Next** to continue.
6. Select **Install**.
7. Select **Finish** to complete the installation.

This installs the nShield CodeSafe 5 SDK `C:\Program Files\nCipher\nfast\c\csd5` and the nShield CodeSafe 5 SDK Python files to `C:\Program Files\nCipher\nfast\python3\csd5`.

5. nShield 5c Codesafe 5 Configuration

To use CodeSafe 5 with nShield 5c, launcher service keys must be exchanged between the client machine and the nShield 5c. These keys are essential for secure communication and access to the launcher service on the module.

If the [automatic configuration and loading](#) is used from a privileged client of the nShield 5c, this key exchange is done automatically with no extra user intervention required, provided that the nShield 5c Connect image is at least v13.7.

See [CodeSafe setup for the nShield 5c](#) for more information about manual setup where required (for unprivileged clients, where not using the automatic configuration, or when using an older Connect image)

6. Build CodeSafe 5 SDK apps

6.1. General SDK use

The CodeSafe 5 SDK provides the tools necessary to build and run SEE machines on nShield 5 HSMs. The CodeSafe 5 SEE machines are containerized. The SDK provides the structure of the container, including a root file system, libraries required for communication with the nCore API, and libraries to enable communication between the SEE machine and the host. The SDK provides headers and libraries for building applications and a root file system for the container containing runtime libraries, binary tools such as `touch`, `cat`, `grep` and optionally a Python distribution.

6.2. Prerequisites

GCC 8.x or later.

6.3. SDK file structure overview

6.3.1. SDK location

The default installation location of the CodeSafe 5 SDK is:

- **Linux:** `/opt/nfast/c/csd5/`
- **Windows:** `C:\Program Files\nCipher\nfast\c\csd5\`

Some tools required for SEE machine operations might be found elsewhere in the main install. For example, `csadmin`, which enables loading, starting, and stopping SEE machines, is installed in the following default locations:

- **Linux:** `/opt/nfast/bin/csadmin`
- **Windows:** `C:\Program Files\nCipher\nfast\bin\csadmin` (Windows)

These cases are described in the following sections as required.

6.3.2. Container root file system

The container root file system is located in:

- **Linux:** `/opt/nfast/c/csd5/rootfs/`

- **Windows:** `C:\Program Files\nCipher\nfast\c\csd5\rootfs\`

This root file system contains two main parts: binary files and libraries.

6.3.2.1. Binaries

`rootfs/bin/` (Linux) or `rootfs\bin\` (Windows) contains many useful common Linux binaries that you might need within the container such as `cat`, `grep`, and `touch`.

`rootfs/sbin/` (Linux) or `rootfs\sbin\` (Windows) contains the `init` script for the container.

6.3.2.2. Libraries

`rootfs/lib/` and `rootfs/usr/lib/` (Linux) or `rootfs\lib\` and `rootfs\usr\lib\` (Windows) contain runtime libraries that may be needed by applications built with the SDK.

6.3.3. CMake

The SDK installs a directory which includes CMake toolchains used for building example SEE machines:

- **Linux:** `/opt/nfast/c/csd5/cmake`
- **Windows:** `C:\Program Files\nCipher\nfast\c\csd5\cmake`

These toolchains can serve as examples themselves for creating custom toolchains.

6.3.4. Include directories

The SDK provides two directories with header files that can be included along with their respective libraries to provide additional functionality in SEE machines. These headers are stored in:

- **Linux:**
 - `/opt/nfast/c/csd5/gcc/*`
 - `/opt/nfast/c/csd5/include-see/*`
- **Windows:**
 - `C:\Program Files\nCipher\nfast\c\csd5\gcc*`
 - `C:\Program Files\nCipher\nfast\c\csd5\include-see*`

6.3.5. SEE specific libraries

The C libraries which are specific to SEE machines, including `seelib.a` and `librtusr.a`, are located in:

- **Linux:** `/opt/nfast/c/csd5/lib-ppc64-linux-musl/*`
- **Windows:** `C:\Program Files\nCipher\nfast\c\csd5\lib-ppc64-linux-musl*`

These libraries must be included to enable critical SEE machine functionality such as communication with the nCore API.

The Python module specific to SEE machines is `seeapi.py`. This module is located under Python site packages in `nshield.ipcdaemon.seeapi`. This must be imported as `SEEAPI` to enable critical SEE machine functionality such as communication with the nCore API.

6.3.6. Compatibility

The CodeSafe 5 SDK and nShield 5 HSMs are sufficiently different from previous implementations that applications for HSM models cannot run on the nShield 5.

Applications must be rebuilt using the CodeSafe 5 SDK to run on the nShield 5.

Where possible, APIs such as SEElib and SEEJobs behave as they did with previous HSM models, but signing and deployment details for CodeSafe 5 applications differ.

6.4. Building new SEE machines with SEElib

An SEE machine is a container image with a complete filesystem which can be loaded onto an CodeSafe 5-enabled HSM as part of a container. The SEElib library enables SEE machines to interface with the nCore API via the IPC daemon.

Source code is compiled using one of the GCC cross-compilers supplied with the CodeSafe SDK. For details of required compiler options, toolchains, makefiles and so on, see the CMake files supplied with the examples, as well as [Build and sign example SEE machines on Linux](#) and [Build and sign example SEE machines on Windows](#).

The container image must be signed using the `csadmin` utility tool.

6.4.1. Developer authentication

CodeSafe 5 requires a signed CodeSafe image to run SEE machines on the HSM.

The CodeSafe developer needs to request a developer ID certificate by sending a Certifi-

cate Signing Request (CSR) to Entrust support. The tool used to create the CSR is integrated into the HSM software as a subcommand of `csadmin` utility.

For security purposes, a developer keypair must be created and stored within the HSM. In addition, the keypair must be OCS protected to provide authorization control on its use. The developer keypair will be created by `csadmin` if it does not already exist.

After the certificates are received, they are installed on the HSM and are used to sign Code Safe application images with the `csadmin` tool.

The implementation of this is described in more detail in [Sign and deploy CodeSafe 5 SDK apps using csadmin](#).

6.4.2. Deploying SEE machines

After the code has been compiled, built, and signed, the `csadmin` utility tool is used to deploy the SEE machine. It is used to load the signed CodeSafe application image and then to start the SEE machine. The SEE machine then runs the `entrypoint` including the `main()` function.

For more information on the `csadmin` utility, see [Sign and deploy CodeSafe 5 SDK apps using csadmin](#).

6.4.3. SEE machine initialization requirements

An SEE machine must initialize the `SEELib` before making use of any of the `SEELib` functionality. This is done by calling `SEELib_init()`. It is recommended that this call is made immediately within the `main()` function of an SEE machine.

By default, `SEELib_init()` will also enable SEEJobs support for communication from the host via `Cmd_SEEJob` and `Cmd_FastSEEJob` sent via a client hardserver. This uses port `8888` within the container, and this port should be set as the `ssh_tunnel` port in the container configuration as shown in later examples. It is possible to enable a non-default port for SEEJobs by calling `SEELib_SetPort(8000)` (for example) before `SEELib_init()`. To disable SEEJobs listening altogether, run `SEELib_SetPort(0)` before `SEELib_init()`

6.4.4. SEELib Functions

After initialization, `SEELib` functions can be used to communicate with the nCore API via the IPC daemon that is included as part of the container image. These functions behave the same as in previous CodeSafe versions although the underlying implementation has

changed.

6.4.4.1. SEELib_Transact()

To send a command to the nCore API and block waiting for a reply:

```
int SEELib_Transact(struct M_Command *cmd, struct M_Reply *reply)
```

This sends the **cmd** command to the nCore API and waits for the reply to be written to **reply**.

6.4.4.2. SEELib_Submit() / SEELib_Query()

To send a non-blocking command to the nCore API:

```
int SEELib_Submit(M_Command *cmd, M_Reply *reply, PEVENT ev, SEELib_ContextHandle tctx)
```

The **cmd** command is submitted to the nCore API. The transaction listener thread will call EventSet **ev**, if **ev** is non-NULL when the reply returns for this command. The reply is unmarshalled into **reply** and **tctx** is returned to the caller with **SEELib_Query(M_Reply **replyp, SEELib_ContextHandle *tctx_r)**.

Before using the **SEELib_Submit()** method, **SEELib_StartTransactListener()** must have been called to start the transaction listener.



Unlike **SEELib_SubmitCoreJob()**, **SEELib_Submit()** does not block and wait for all other calls to **SEELib_Transact()** to complete.

6.4.4.3. SEELib_SubmitCoreJob / SEELib_GetCoreJobEx()

To submit a job to the nCore API:

```
extern int SEELib_SubmitCoreJob(const unsigned char *data, unsigned int len)
```

To receive a job from the nCore API:

```
extern int SEELib_GetCoreJobEx(unsigned char *buf, M_Word *len_io, unsigned flags)
```

SEELib_SubmitCoreJob() is blocking. It waits for the job to be submitted, which includes waiting for existing calls made to **SEELib_Transact()** to be completed. The same is true for **SEELib_GetCoreJobEx()**.

For non-blocking calls, consider using `SEELib_Submit()`.

6.4.4.4. Other SEELib methods

For a comprehensive list of all functionality provided via the SEELib, see: [SEE API documentation](#).

6.4.5. Host/SEE machine communication

Host/SEE machine communication can be done using SEEJobs via the hardserver using an automatically configured SSH tunnel set up by using the `[codesafe]` configuration section of the client-side `config` file. Alternatively (or additionally) communication between the host and the SEE machine can be done via TCP and UDP IPv6 networking.



The `ncoreapi` service can only connect to one CodeSafe container at a time.

6.4.5.1. Update Connects running in an IPv4 context

The host side of the CodeSafe 5 examples will only be able to communicate over IPv6. Connects running in an IPv4 context will not be able to run examples without changing how CodeSafe 5 is configured on the Connect. See [nShield HSMs with CodeSafe / CodeSafe 5](#) for more information.

6.5. Compatibility layer for legacy SEE machines

The CodeSafe 5 SDK provides libraries for developing new SEE machines. It also provides libraries, files, and headers designed for maintaining backwards compatibility with legacy CodeSafe SEE machines. SEE machines built with the compatibility layer work with the C interface and the [Java](#) interface.



Do not use the compatibility layer libraries, files, and headers to create new SEE machines. They are only supplied to allow legacy applications to be quickly re-compiled and run on nShield 5 HSMs.

The requirement for a compatibility layer arises from changes made to the overall structure of how CodeSafe 5 SEE machines interact with both the host and with the nCore API:

- Host-SEE machine communication

In legacy CodeSafe implementations, for older HSMs, communication between a host-

side application and an SEE machine would be done via the nCore API using [SEEJobs](#). Using the nCore API to relay [SEEJobs](#) between the host-side and the SEE machine is no longer supported.

Communication via the nCore API has been replaced with direct communication between the host and SEE machine using TCP/UDP socket connections. Optionally, communication can be over an SSH tunnel for security. This allows greater control of the creation, management, and use of connections between the host and SEE machine for developers. It also improves performance as [SEEJobs](#) no longer have to be sent to the nCore API before being forwarded to the SEE machine.

- SEE machine - nCore API communication

Communication between the host and SEE machine no longer requires the nCore API as an intermediary. Communication intended to be exclusively between the SEE machine and the nCore API has also changed with the addition of the container IPC daemon. The IPC daemon is provided by Entrust, exists within the container, and maintains connections between the container and the nCore API.

The IPC daemon forwards commands to the nCore API sent using the [SEELib](#). Outside of the addition of the intermediary forwarder, the communication between the SEE machine and the nCore API remains functionally unchanged.

The [ncoreapi](#) service can only connect to one CodeSafe container at a time.

The compatibility layer contains two main parts:

- [liblegacy_compatibility.a](#), the module-side library.
- [include-see/legacy-compatibility-host/*](#), the host-side compatibility interface.

6.5.1. Module-side compatibility layer

The module-side compatibility layer provides the methods necessary to connect the SEE machine to the host-side application via network connection.

The module-side compatibility layer comprises the [liblegacy_compatibility.a](#) library. Its install location is:

- **Linux:** [/opt/nfast/c/csd5/lib-ppc64-linux-musl/](#)
- **Windows:** [C:\Program Files\Ncipher\nfast\c\csd5\lib-ppc64-linux-musl\](#)

Legacy SEE machines must be built with [liblegacy_compatibility.a](#). When initialized, the module-side compatibility layer opens and maintains a connection between the host-side application and the SEE machine. This allows legacy applications to continue using [SEEL-](#)

`ib_AwaitJob()` and `SEELib_ReturnJob()` to accept incoming jobs and return them to the host-side application when completed.

6.5.2. Host-side compatibility layer

The host-side compatibility layer provides the methods necessary to connect the host-side application to the SEE machine via network connection.

The host-side compatibility layer comprises the following files:

- `legacy-csee-host-side-compatibility.h` contains all necessary function declarations.
- `legacy-csee-host-side-compatibility.c` contains required host-side function definitions required to connect to and maintain the connection to legacy SEE machines.

Their install location is:

- **Linux:** `/opt/nfast/c/csd5/examples/csee/utils/hostside/`
- **Windows:** `C:\Program Files\nCipher\nfast\c\csd5\examples\csee\utils\hostside\`

Legacy host-side applications must be built with `legacy-csee-host-side-compatibility.h` and `legacy-csee-host-side-compatibility.c`. This is done by emulating the connection which was previously created and managed by the hardserver and the nCore API.

`legacy-csee-host-side-compatibility.c` is compiled and added to the `libutil.a` library. Applications should link to it if they need to connect to legacy SEE machines.

6.5.3. Initialize module-side compatibility

Initialize the module-side compatibility layer:

```
extern void SEELib_Legacy_Support_Init(const char* PORT)
```

See Classic SEE (CSEE) examples in [Port existing CodeSafe application to CodeSafe 5](#) for how the module-side legacy support can be initialized to open a socket connection at port `PORT` to communicate between host-side and SEE machines.

6.5.4. Use module-side compatibility

Legacy applications expect incoming messages from the host to be piped from the host to the nCore API via the hardserver. From there, they eventually become accessible within the SEE machine via calls to `SEELib_AwaitJob()` and `SEELib_ReturnJob()`. After the module-side

compatibility layer is initialized (see [Initialize module-side compatibility](#)), these functions will work exactly as they have in previous CodeSafe applications. No further changes are necessary.

Initializing the compatibility layer functionality via the `SEELib_Legacy_Support_Init()` call allows the compatibility layer to handle incoming and outgoing jobs as would previously have been done by the nCore API. The Classic SEE (CSEE) examples show that the only change made to the SEE machines to allow for backwards compatibility is the initialization of the compatibility layer.



The compatibility layer only supports one client connection at a time while the hardserver can support many.

6.5.5. Initialize host-side application compatibility

Initialize the host-side legacy application to allow connection to the SEE machine, communicating to the host via `PORT`:

```
netsee_initialize_legacy_seejob_support(const char * cseeContainerMachineIPv6, const char *
cseeContainerMachinePort)`
```

Here, `cseeContainerMachinePort` must match the `PORT` initialized by the SEE machine. `cseeContainerMachineIPv6` is the container's IPv6 address. See the execution of CSEE examples in [Port existing CodeSafe application to CodeSafe 5](#) for more information on passing in the IPv6 address of the container.

`netsee_initialize_legacy_seejob_support()` establishes a connection to the SEE machine's container at port `cseeContainerMachinePort`. The compatibility layer maintains this connection and handles the sending of SEEJobs between the host and module SEE machine.

6.5.6. Use host-side application compatibility

The compatibility layer allows host-side application calls to interact with the SEE machine to remain largely unchanged. Some changes to calls are, however, required. These changes, rather than changing how the functions operate, largely serve to remove no longer required elements, such as `NFastApp_Connection`.

- `netsee_transact_legacy_seejob(const M_Command *command, M_Reply *reply, struct NFast_Transaction_Context *tctx)`

replaces:

```
NFastApp_Transact(NFastApp_Connection conn, struct NFast_Call_Context *cctx,
const M_Command *command, M_Reply *reply, struct NFast_Transaction_Context
*tctx)
```



The NFastApp_Connection and NFast_Call_Context are no longer required and should not be passed in.

- `netsee_simple_transact_legacy_seejob(const M_Command *cmd, M_Reply *reply, int fatal)`

replaces:

```
simple_transact (NFastApp_Connection nc, M_Command *pcmd, M_Reply *preply,
int fatal)
```



The NFastApp_Connection is no longer required and should not be passed in.

- `netsee_submit_legacy_seejob(const M_Command *cmd, M_Reply *reply, struct NFast_Transaction_Context *tctx)`

replaces:

```
NFastApp_Submit(NFastApp_Connection conn, struct NFast_Call_Context *cctx,
const M_Command *command, M_Reply *reply, struct NFast_Transaction_Context
*tctx)
```



The NFastApp_Connection and NFast_Call_Context are no longer required and should not be passed in.

- `netsee_wait_legacy_seejob(M_Reply **replay, struct NFast_Transaction_Context **tctx)`

replaces:

```
NFastApp_Wait(NFastApp_Connection conn, struct NFast_Call_Context *cctx, M_Re-
ply **replay, struct NFast_Transaction_Context **tctx_r)
```



The NFastApp_Connection and NFast_Call_Context are no longer required and should not be passed in.

With these changes implemented, legacy host-side applications, when run in conjunction with an SEE machine properly initialized with `liblegacy_compatibility.a`, should function identically to when run in previous implementations of CodeSafe.



This section demonstrated how to use the compatibility layer to quickly bring legacy applications into the new CodeSafe 5 environment. New

applications should never be written with the compatibility layer. It is advised that, when possible, a user defined TCP/IPv6 network connection between the host-side application and the SEE machine is implemented, rather than using the compatibility layer to transact jobs. However, the compatibility layer does perform this job when no such custom implementation can be made.

7. Sign and deploy CodeSafe 5 SDK apps using csadmin

7.1. Signing CodeSafe images

All CodeSafe images must be signed before they can be loaded on to an HSM. Entrust recommends that you have two signing keys: one that you use to sign CodeSafe images that are still under development, and one that you only use for signing tested CodeSafe images that are ready for deployment. In this guide, the two recommended keys are referred to as the development signing key and the production signing key, however you can name these keys as required by your particular development organisation.



Signed CodeSafe images can be loaded to an HSM if the certificate associated with the signing key is also loaded to that HSM. Therefore you must ensure that the certificates associated with development signing keys are never distributed outside of your development organisation. If you develop CodeSafe images for customers who are not part of your development organisation, you should only send them CodeSafe images that have been signed by, and certificates that are associated with, a production signing key.

You can create as many signing keys as you require. This allows you to use different signing keys to group your CodeSafe images based on whatever criteria you require. For example, you could use different signing keys based on the intended customer or on the functionality of the CodeSafe image.

You must keep track of which key has been used to sign which image and ensure that the end user receives the correct matching certificate and does not receive certificates that they do not require.



Unless stated otherwise, the signing keys mentioned in this page are Application Signing Keys (ASK). Signatures using non-Application Signing Keys (non-ASK) are also accepted by the HSM, granting specific key access to an authorized CodeSafe application.

The following sections describe the commands used to create the signing keys and certificates followed by a worked example showing the entire process of building, signing, loading, and running a CodeSafe image.

7.2. The csadmin utility tool



The following examples use a Linux machine for the deployment of CodeSafe applications. The same commands can be applied to a Windows machine.

The **csadmin** tool is used to manage CodeSafe images throughout the development and deployment process. It is available as part of the Security World ISO. It must be installed as instructed in [Install the CodeSafe 5 SDK on Linux](#) and [Install the CodeSafe 5 SDK on Windows](#).

You must be logged in as an Administrator or a user with local administrator rights to execute **csadmin** commands.

You must have `/opt/nfast/bin` in your **PATH** environment variable to use **csadmin**.

Executing **csadmin** displays the available subcommands.

To view the help text included here while using **csadmin**, run a command or sub-command with the `-h|--help` option.



The **csadmin** tool covers CodeSafe application deployment from both the perspective of a CodeSafe application developer and a CodeSafe application user. The help text displays the complete set of commands available. This document details the commands that are specific to CodeSafe developers. See [csadmin](#) for an overview of the **csadmin** tool and details of the other commands available.

7.2.1. Generate loadable images

CS5 images are generated with **csadmin image generate**. Before generating an image, the CodeSafe 5 SDK must be previously installed. This includes an installation of Python and nfpython suitable to run on the HSM. To display the **generate** operation's usage, execute it with the `--help` option :

```
$ csadmin image generate --help
usage: csadmin image generate [-h] --package-name PACKAGE_NAME --version-str VERSION_STR --entry-point
ENTRY_POINT --network-conf NETWORK_CONF
--packages-conf PACKAGES_CONF --rootdir ROOTDIR [--verbose] CS5FILE

positional arguments:
  CS5FILE                The cs5 file to be handled

optional arguments:
  -h, --help            show this help message and exit
  --package-name PACKAGE_NAME
                        Short name describing the product contents
```



```

--version-str VERSION_STR
    Version number of this package contents
--entry-point ENTRY_POINT
    Full path, within the container, to the entry point application to be executed upon start
--network-conf NETWORK_CONF
    Full path, outside the container, to the network config file to be copied into the
container meta data
--packages-conf PACKAGES_CONF
    Full path, outside the container, to the extra packages config file used to copy
additional packages into container rootfs
--rootdir ROOTDIR
    Directory where the contents of the new container are located
--verbose
    Print verbose logs

```

Generating an image requires the name of the CS5 file and the use of the following mandatory command-line arguments:

- `--package-name`
- `--version-str`
- `--entry-point`
- `--network-conf`
- `--packages-conf`
- `--rootdir`

The following items are also required:

- A container directory (not necessarily named "container") that points to what would be the SEE machine's root directory.

This directory must include any files used by the application, including the entry point program, for example:

```

container/
├── home
├── usr
│   └── bin
│       └── entrypoint

```

The container directory can be located anywhere in the host file system. Ensure you pass the full path to the `generate` command via the `--rootdir` argument, as specified in the command usage.

- An entry point program.

This is the program that runs when the SEE container is started (on launcher start). It must be made executable so it can be launched accordingly. In the previous example, the entry point program is in `container/usr/bin/entrypoint`.

- A network configuration file. (See [Example network-conf.json file](#).)

The valid range for `container_port` is 1024 - 65535.

- A file with extra packages information. (See [Example extra-packages-conf.json file](#))

7.2.1.1. Example csadmin image generate operation

```
$ csadmin image generate --package-name "MyCodeSafeApp" --entry-point /usr/bin/entrypoint --network-conf network-  
conf.json --packages-conf extra-packages-conf.json --version-str 1.0 --rootdir container/ myapp.cs5  
INFO: creating content package  
INFO: Creating content tar ball  
INFO: Creating copy of source file: network-conf.json into dest: cs5_build/meta/network-conf.json  
INFO: Creating copy of source file: extra-packages-conf.json into dest: cs5_build/meta/extra-packages-conf.json  
INFO: Creating compressed tar ball cs5_build/extra-packages.tar.gz out of cs5_build/extra-packages  
INFO: Creating compressed tar ball cs5_build/container.tar.gz out of container/  
INFO: Creating uncompressed tar ball content.tar out of cs5_build  
INFO: creating cs5 file myapp.cs5  
INFO: adding content hash to the package  
  
INFO: File myapp.cs5 was created successfully!
```

`--entry-point` points to the full path of the executable program relative to the container's root.

7.2.1.2. Example extra-packages-conf.json file

```
{
  "packages": [
    {
      "package": "python",
      "description": "python 3.8 binaries",
      "host_path": "python3/csd5/ppc64/usr/bin",
      "machine_path": "usr/bin",
      "exclude": ""
    },
    {
      "package": "python",
      "description": "python 3.8 libraries",
      "host_path": "python3/csd5/ppc64/usr/lib/python3.8",
      "machine_path": "python3",
      "exclude": ""
    },
    {
      "package": "binaries",
      "description": "binaries for script support 1.0.0",
      "host_path": "c/csd5/rootfs/bin",
      "machine_path": "bin",
      "exclude": ""
    }
  ]
}
```

7.2.1.3. Example network-conf.json file

```
{
  "incoming" : {
    "tcp" : {
      "protos" : [ "ipv6" ], "ports" : [ 8000, 8001, 8888 ]
    }
  },
  "outgoing" : {
    "udp" : {
      "protos" : [ "ipv4" ], "ports" : [ 53 ]
    }
  },
  "ssh_tunnel" : {
    "container_port" : 8000
  }
}
```

7.2.1.4. Example entry point script

```
#!/bin/sh
export PYTHONHOME=/usr/bin
export PYTHONPATH=/usr/lib/python3.8:/usr/lib/python3.8/lib-dynload:/usr/lib/python3.8/site-packages
python -m http.server --directory / --bind :: 8888
```

7.2.2. Sign images

All images must be signed with an application signing key (ASK), however, optionally,

images can also be signed with multiple, non-application signing keys (non-ASK).

7.2.2.1. Signing with an application signing key

CodeSafe images are signed with **csadmin image sign**. A signing key must be created before the CS5 file is signed, because signing must be done using HSM-protected keys.

```
csadmin image sign --help
usage: csadmin image sign [-h] --askeyname ASKEYNAME --devkeyname DEVKEYNAME --devcert DEVCERT [--startdate STARTDATE] [--expirydate EXPIRYDATE]
                           [--out OUT] [--verbose]
                           CS5FILE

positional arguments:
  CS5FILE                The cs5 file to be signed

options:
  -h, --help              show this help message and exit
  --askeyname ASKEYNAME   Name (ident) of the application signing key
  --devkeyname DEVKEYNAME Name (ident) of the developer signing key
  --devcert DEVCERT       The signed developer certificate PEM file
  --startdate STARTDATE   Start of validity period for the signed ASK cert in Unix time (default: no start date)
  --expirydate EXPIRYDATE End of validity period for the signed ASK cert in Unix time (default: no expiration date)
  --out OUT               Name of the output file. If not specified, the cs5 file is overwritten.
  --verbose               Print verbose logs
```

For more information, see [Signing CodeSafe images](#).

7.2.2.2. Signing with a non-application signing key

CodeSafe images can also be signed with **csadmin image signextra**. Additional signing uses keys other than application signing keys, such as SEEInteg keys. A signing key must be created before the CS5 file is signed, because signing must be done using HSM-protected keys.

```
csadmin image signextra --help
usage: csadmin image signextra --appname APPNAME --key KEY [--keymech {SHA256Hash,SHA384Hash,SHA3b256Hash,SHA3b384Hash,SHA3b512Hash,SHA512Hash}]
                           [--out OUT] [--verbose]
                           CS5FILE

positional arguments:
  CS5FILE                The cs5 file to be signed

options:
  -h, --help              show this help message and exit
  --appname APPNAME       Value to use for the appname (default simple)
  --key KEY               Name (ident) of the signing key
  --keymech {SHA256Hash,SHA384Hash,SHA3b256Hash,SHA3b384Hash,SHA3b512Hash,SHA512Hash}
                           Key hashing mechanism (default SHA512Hash).
  --out OUT               Name of the output file. If not specified, the cs5 file is overwritten
```

```
--verbose      Print verbose logs
```

For more information, see [Signing CodeSafe images](#).

7.2.3. Create a developer ID certificate

Developer ID certificates are created with `csadmin ids create`. This command generates a developer ID key with the given name (if it doesn't exist already) and a certificate signing request so a certificate can be generated (see [Signing CodeSafe images](#)):

```
$ csadmin ids create --help
usage: csadmin ids create [-h] --keyname KEYNAME [-m MODULE] --x509cname COMMON_NAME [--x509country COUNTRY]
                        [--x509province STATE_OR_PROVINCE] [--x509locality LOCALITY] --x509org ORGANIZATION [--
x509orgunit ORGANIZATIONAL_UNIT] [--verbose]

options:
  -h, --help            show this help message and exit
  --keyname KEYNAME      Name for the certificate's key.
  -m MODULE, --module MODULE
                        Module to generate the key with.
  --x509cname COMMON_NAME
                        The CN part of the key's DN.
  --x509country COUNTRY
                        The C part of the key's DN.
  --x509province STATE_OR_PROVINCE
                        The ST part of the key's DN.
  --x509locality LOCALITY
                        The L part of the key's DN.
  --x509org ORGANIZATION
                        The O part of the key's DN.
  --x509orgunit ORGANIZATIONAL_UNIT
                        The OU part of the key's DN.
  --verbose             Print verbose logs
```

7.3. Example CodeSafe developer process

The examples in this chapter show how various `csadmin` commands can be used to create a signed CodeSafe image for deployment. For details of the `csadmin` tool (See [The csadmin utility tool](#))

7.3.1. Create developer ID keys

To sign CodeSafe images, you must create a developer ID for your development organisation and obtain a matching certificate from Entrust. You can obtain a certificate by creating a Certificate Signing Request (CSR) file and sending it to Entrust Support who will process the CSR and return a signed certificate to you.



Entrust strongly recommend that you create at least two developer IDs:

a 'development' ID for signing CodeSafe images that are still in development, and a 'production' ID for signing images that are ready to be deployed.

The `csadmin ids create` command provides the functionality to generate a developer ID key if it does not already exist, as well as the CSR file in a single step.



Keep track of which certificate matches each developer ID key. When you send a signed CodeSafe image to a customer you will need to also send them the matching certificate for them to be able to load the image on their HSM.

The developer ID keys only need to be created once. The certificates matching them have a limited validity period and will need to be refreshed before they expire.



When you refresh a certificate you must send it to anyone who received a copy of a SEE machine that is signed by the key matching that certificate. Users of SEE machines require a valid certificate every time they start the SEE machine.

To refresh a certificate, use the `csadmin ids create` command with an existing key. This creates a CSR file for the existing key, which should be sent to Entrust Support who will process the CSR and return a new signed certificate.

The integrity of the signing process relies on the procedural steps being followed to secure a CodeSafe application image.

For this reason, developer ID keys are OCS protected and therefore to sign a CodeSafe application a quorum of OCS cards and associated passphrases must be available for the signing.



Only use your 'production' developer ID key to sign fully tested CodeSafe images that you know to be ready for deployment.

7.3.1.1. Generate an HSM-protected developer ID key and CSR

```
csadmin ids create --keyname developerid --x509cname developer.entrust.com --x509country US --x509province
Minnesota --x509locality Shakopee --x509org "CodeSafe App Development" --x509orgunit "Entrust CodeSafe"
```

Generate key 'testdeveloperkey' ...

Loading 'TestOCS':

Module 1: 0 cards of 1 read

Module 1 slot 0: empty

Card reading complete.

OK

Generate a CSR in 'testdeveloperkey.csr' ...

OK

Created CSR file 'testdeveloperkey.csr'. Please send it to Entrust Support



This creates the CSR file in the location where the command was run.



keyname must conform with character set restrictions. For more information, see **ident** in the [Key properties](#) table.



This developer ID creation was done with **TestOCS**, quorum of 1/1. Exact output might vary slightly with different OCS quorums.

Send the resulting CSR to customer support to be signed by Entrust.

7.3.2. Load your certificate

When you receive your signed certificate chain back from Entrust Support, load the developer ID certificate chain in the HSM using **csadmin ids add**.

You can use **csadmin ids list** to view the loaded certificate.

```
$ csadmin ids add entrust_developerid_cert_chain.pem
FEDC-BA09-8765      SUCCESS
$ csadmin ids list
FEDC-BA09-8765      SUCCESS
Certificates:
{'serialNumber': '1', 'subject': 'Common Name: developer.entrust.com, Organizational Unit: Entrust CodeSafe,
Organization: Entrust, Locality: Shakopee, State/Province: Minnesota, Country: US', 'keyid':
'abcdef12345678900987654321fedcbaabcdef12', 'authKeyid': '0987654321fedcbaabcdef123456789009876543', 'notBefore':
'2023-01-01 12:34:56+00:00', 'notAfter': '2024-01-01 12:34:56+00:00'}
{'serialNumber': '2', 'subject': 'Common Name: developer.entrust.com, Organizational Unit: Entrust CodeSafe,
Organization: Entrust, Locality: Shakopee, State/Province: Minnesota, Country: US', 'keyid':
'1234567890abcdef1234567890098765432112345678', 'authKeyid': 'fedcba09876543211234567890abcdef1234567890', 'notBefore':
'2023-01-01 12:34:56+00:00', 'notAfter': '2024-01-01 12:34:56+00:00'}
```

7.3.2.1. Generate an Application Signing Key (ASK) with generatekey

This generates a simple ECDSA NIST521P key.

The following example specifies the key to be protected with an OCS.

```
/opt/nfast/bin/generatekey --batch --module=1 simple type=ECDSA curve=NISTP521 ident=ask plainname=ask  
protect=token
```

7.3.2.2. Sign the CodeSafe image using an ASK key

This example signs a CodeSafe application called **hello.cs5**:

```
csadmin image sign --askeyname ask --devkeyname developerid --devcert ~/ca/developerid_cert.pem --out ~/hello-  
signed.cs5 ~/hello.cs5
```

7.3.2.3. Sign the CodeSafe image using a non-ASK key

This example signs a CodeSafe application called **hello.cs5** using a key named **seeintkey-name** that was generated by **generatekey**:

```
csadmin image signextra --appname seeinteg --key seeintkeyname --keymech SHA512Hash --out ~/hello-signed-  
extra.cs5 ~/hello.cs5
```


8. Build and sign example SEE machines on Linux

8.1. Build module-side C examples

1. Create an empty directory to build the module side examples into, for example:

```
mkdir ~/buildmodule/
```

2. Navigate to the empty directory:

```
cd ~/buildmodule/
```

3. Build the module side examples with **cmake** using the following commands:

```
cmake -DCMAKE_TOOLCHAIN_FILE=/opt/nfast/c/csd5/cmake/codesafe-toolchain-nshield5-csee.cmake  
/opt/nfast/c/csd5/examples/  
  
cmake --build .
```

Successful builds create **.cs5** images for each example. For example, the classic SEE **Hello** example has a **.cs5** image at **~/buildmodule/n5/csee/hello/module/hello.cs5**.

8.2. Building Host Side C Examples

1. Create an empty directory to build the host-side clients for the SEE machines, for example:

```
mkdir ~/buildhost/
```

2. Navigate to the directory where the host-side examples will be built:

```
cd ~/buildhost/
```

3. Build the host-side examples with **cmake** using the following commands:

```
cmake /opt/nfast/c/csd5/examples/  
  
cmake --build .
```

Successful builds create executable host-side clients for each example. For example, the

classic SEE **Hello** example has an executable program at `~/build-host/n5/csee/hello/host/hello`.

8.3. Build CS5 Images for Python Examples

1. Create an empty directory to build the Python examples into, for example:

```
mkdir ~/build_python
```

2. Navigate to the empty directory:

```
cd ~/build_python/
```

3. Build the examples with **cmake** using the following commands:

```
cmake /opt/nfast/python3/csd5/examples
cmake --build .
```

Successful builds create **.cs5** images and executable host-side clients for each example. For example, the **hello_tcp** example has a **.cs5** image at `~/build_python/n5/netsee/helloworld_tcp/module/helloworld_mod_tcp.cs5` and the executable program is located at `~/build_python/n5/netsee/helloworld_tcp/hostside/helloworld_host_tcp.py`.

8.4. Sign CodeSafe Images

1. Use **csadmin ids create** to generate the developer ID key, if it does not already exist, as well as the CSR file in a single step. If the key already exists, it only generates the CSR.

```
csadmin ids create --keyname developerid --x509cname developer.entrust.com --x509country US --x509province
Minnesota --x509locality Shakopee --x509org "Entrust CodeSafe" --x509orgunit "Entrust CodeSafe"

Generate key 'testdeveloperkey' ...

Loading 'TestOCS':
Module 1: 0 cards of 1 read
Module 1 slot 0: empty
Card reading complete.

OK
Generate a CSR in 'testdeveloperkey.csr' ...
OK
Created CSR file 'testdeveloperkey.csr'. Please send it to Entrust Support
```



This creates the CSR file in the location where the command was

run. This developer ID creation was done with **TestOCS**, quorum of 1/1. Exact output might vary slightly with different OCS quorums.

2. Send the CSR to customer support to be signed by Entrust. You must obtain the signed developer ID certificate in order to sign and load an application.



For more detailed information on Developer IDs and CSRs, see [Sign and deploy CodeSafe 5 SDK apps using csadmin](#).

3. Use **nfast generatekey** to generate a simple ECDSA NIST521P application signing key (ASK). The following example specifies the key to be protected by the module. However, end users are encouraged to protect the key with an OCS.

```
/opt/nfast/bin/generatekey --batch --module=1 simple type=ECDSA curve=NISTP521 ident=ask plainname=ask protect=module
```

4. Sign the CodeSafe image, for example:

```
csadmin image sign --askeyname ask --devkeyname developerid --devcert ~/ca/developerid_cert.pem --out /tmp/hello-signed.cs5 ~/ca/hello.cs5
```

Additional examples are provided later in this chapter.

5. Where applicable, sign the CodeSafe image with non-ASK keys, for example:

```
csadmin image signextra --appname seeinteg --key seeintkeyname --out /tmp/hello-signed-extra.cs5 /tmp/hello-signed.cs5
```

6. Use **csadmin ids add** to install the developer ID certificate chain from Entrust.

You can use **csadmin ids list** to view the loaded certificate.

```
$ csadmin ids add entrust_developerid_cert_chain.pem
FEDC-BA09-8765 SUCCESS
$ csadmin ids list
FEDC-BA09-8765 SUCCESS
Certificates:
{'serialNumber': '1', 'subject': 'Common Name: developer.entrust.com, Organizational Unit: Entrust CodeSafe, Organization: Entrust, Locality: Shakopee, State/Province: Minnesota, Country: US', 'keyid': 'abcdef12345678900987654321fedcbaabcdef12', 'authKeyid': '0987654321fedcbaabcdef123456789009876543', 'notBefore': '2023-01-01 12:34:56+00:00', 'notAfter': '2024-01-01 12:34:56+00:00'}
{'serialNumber': '2', 'subject': 'Common Name: developer.entrust.com, Organizational Unit: Entrust CodeSafe, Organization: Entrust, Locality: Shakopee, State/Province: Minnesota, Country: US', 'keyid': '1234567890abcdeffedcba098765432112345678', 'authKeyid': 'fedcba09876543211234567890abcdeffedca098', 'notBefore': '2023-01-01 12:34:56+00:00', 'notAfter': '2024-01-01 12:34:56+00:00'}
```

8.5. Run NetSEE examples

NetSEE examples communicate between the client and SEE machine directly via TCP or UDP IPv6 networking to the container, unlike legacy applications, such as for Solo XC or Solo+, which required using an emulation layer on top of SEEJobs to support networking.

8.5.1. helloworld_tcp

To execute the helloworld TCP example that opens a socket within the container and uses the connection to transact a "helloworld" message:

1. Sign the **.cs5** image using **devcert** and **askeys**:

```
csadmin image sign --askeyname ask --devkeyname developerid --devcert ~/ca/developerid_cert.pem --out
~/buildmodule/n5/netsee/helloworld_tcp/module/helloworld_mod_tcp-signed.cs5
~/buildmodule/n5/netsee/helloworld_tcp/module/helloworld_mod_tcp.cs5
```

2. Load the signed **.cs5** image using **csadmin load**:

```
sudo /opt/nfast/bin/csadmin load ~/buildmodule/n5/netsee/helloworld_tcp/module/helloworld_mod_tcp-
signed.cs5
```



The output of **csadmin load** contains the UUID of the loaded container. This UUID will be required for starting the container. The UUID can always be retrieved from the output of **csadmin list**.

3. Start the container using **csadmin start**:

```
sudo /opt/nfast/bin/csadmin start --uuid fedcba09-8765-4321-1234-567890abcdef
```



csadmin list lists the UUIDs of all containers. The IPv6 address of the started container appears in the output of the **csadmin start** command. It can also be found in the output of **csadmin list** and **csadmin stats**.

4. Run the host-side application.

The host-side application takes three positional arguments, the IPv6 address of the container, the port number, and the message to send to the container. The port number used by this example is 8000 by default. The message can be any string of valid characters.

```
~/buildhost/n5/netsee/helloworld_tcp/hostside/helloworld_host_tcp ffff::fff:ffff:ffff:ffff%nshield0 8000
hello_module
```

Expected output:

```
nseeContainerMachineIP=ffff::ffff:ffff:ffff:ffff%nshield0
nseeContainerMachinePort=8000
msg=hello_module
Successful Connection to Socket...
Host>Sending TCP Message-->hello_module
Host>Hello World From HSM!
```



The IPv6 address is link-local and requires the zone index to be appended (typically `%nshield0`).

8.5.1.1. helloworld_tcp for nShield 5c

The process is the same as the 5s example, but the host-side application command will differ. Instead of IPv6, you can use the Connect's IPv4 address:

The examples for the nShield 5c work similarly to the 5s module, but the IP addresses and ports refer to the 5c Connect network. Similarly, for the TCP example, you can use the Connect's IPv4 address:

```
~/buildhost/n5/netsee/helloworld_tcp/hostside/helloworld_host_tcp 192.168.1.100 8000 hello_module
```

Example output:

```
nseeContainerMachineIP=192.168.1.100
nseeContainerMachinePort=8000
msg=hello_module
Successful Connection to Socket...
Host>Sending TCP Message-->hello_module
Host>Hello World From HSM!
```

8.5.2. helloworld_udp

To execute the helloworld UDP example that opens a socket within the container and uses the connection to transact a "helloworld" message:

1. Sign the `.cs5` image using `devcert` and `askeys`:

```
csadmin image sign --askeyname ask --devkeyname developerid --devcert ~/ca/developerid_cert.pem --out
~/buildmodule/n5/netsee/helloworld_udp/module/helloworld_mod_udp-signed.cs5
~/buildmodule/n5/netsee/helloworld_udp/module/helloworld_mod_udp.cs5
```

2. Load the signed container using `csadmin load`:

```
sudo /opt/nfast/bin/csadmin load ~/buildmodule/n5/netsee/helloworld_udp/module/helloworld_mod_udp-
```

```
signed.cs5
```

Example output:

```
FEDC-BA09-8765: Uploading ~/buildmodule/n5/netsee/helloworld_udp/module/helloworld_mod_udp-signed.cs5
FEDC-BA09-8765: creating machine
FEDC-BA09-8765      SUCCESS
UUID: fedcba09-8765-4321-1234-567890abcdef
```



The output of **csadmin load** contains the UUID of the loaded container. This UUID will be required for starting the container. The UUID can always be retrieved from the output of **csadmin list**.

3. Start the container using **csadmin start**:

```
sudo /opt/nfast/bin/csadmin start --uuid fedcba09-8765-4321-1234-567890abcdef
```

Example output:

```
FEDC-BA09-8765      SUCCESS
IP ADDRESS: ffff::fff:ffff:ffff:ffff
```



csadmin list will list the UUIDs of all containers. The IPv6 address of the started container appears in the output of the **csadmin start** command. It can also be found in the output of **csadmin list** and **csadmin stats**.

4. Run the host-side application.

The host-side application takes three positional arguments, the IPv6 address of the container, the port number, and the message to send to the container. The port number used by this example is 8000 by default. The message can be any string of valid characters.

```
~/buildhost/n5/netsee/helloworld_udp/hostside/helloworld_host_udp ffff::fff:ffff:ffff:ffff%nshield0 8000
hello_module
```

Example output:

```
nseeContainerMachineIP=ffff::fff:ffff:ffff:ffff%nshield0
nseeContainerMachinePort=8000
mesg=hello_module
Successful Connection to Socket...
Host>Sending UDP Message-->hello_module
Host>Hello World From HSM!
```



The IPv6 address is link-local and requires the zone index to be appended (typically `%nshield0`).

8.5.2.1. helloworld_udp for 5c

The process is the same as the 5s example, but the host-side application command will differ. Instead of IPv6, you can use the Connect's IPv4 address:

The examples for the nShield 5c work similarly to the 5s module, but the IP addresses and ports refer to the 5c Connect network.

```
~/buildhost/n5/netsee/helloworld_udp/hostside/helloworld_host_udp 192.168.1.100 8000 hello_module
```

Example output:

```
nseeContainerMachineIP=192.168.1.100
nseeContainerMachinePort=8000
msg=hello_module
Successful Connection to Socket...
Host>Sending UDP Message-->hello_module
Host>Hello World From HSM!
```

8.6. Run NetSEE examples via SSH tunnel

NetSEE examples communicate between the client and SEE machine directly through a TCP/IPv6 network connection to the container, unlike legacy applications, such as for Solo XC or Solo+, which communicate through the hardserver to the nCore API.



On the nShield 5c network, the **SSHD listening address** may be an **IPv4** address instead of **IPv6**. Adjustments to the steps below may be needed to accommodate this.

8.6.1. helloworld_tcp via SSH Tunnel

To execute the helloworld TCP example via an SSH Tunnel that opens a socket within the container and uses the connection to transact a "helloworld" message:

1. Create an SSHD key for the hello example:

```
mkdir ~/examplekeys/
ssh-keygen -t ecdsa -f ~/examplekeys/helloworld_tcp_ecdsa_key
```

2. Modify the **network-conf.json** of the **helloworld_tcp** example to support SSH tunnel-

ing, for example:

```
cat ~/buildmodule/n5/netsee/helloworld_tcp/module/network-conf.json
{
  "incoming": {
    "tcp": {
      {
        "protos": ["ipv6"],
        "ports": []
      }
    },
    "outgoing" : {
      "tcp" : {
        {
          "protos": ["ipv6"],
          "ports": []
        }
      },
      "ssh_tunnel" : {
        "container_port" : 8000
      }
    }
  }
}
```

+ When the container server app accepts a client connection on the specified incoming port (for example **8000**), it designates and responds to the client on an ephemeral port in the range **[32768-60999]** as the outgoing port. This port does not have to be defined in the **network-conf.json**. Only one port is supported for the **ssh_tunnel** / **container_port** in this version. The **ssh_tunnel** port must be the only port specified for communication that is restricted to be made over SSH. To only send communication in the plain, the port should instead be specified in the **incoming ports** list.

1. Rebuild the **.cs5** image with the updated **network-conf.json** so the loaded container will allow SSH tunneling:

```
sudo /opt/nfast/bin/csadmin image generate --package-name "helloworld_tcp" --entry-point
/usr/bin/entrypoint --network-conf ~/buildmodule/n5/netsee/helloworld_tcp/module/network-conf.json
--packages-conf ~/buildmodule/n5/netsee/helloworld_tcp/module/extra-packages-conf.json --version-str 1.0
--rootdir ~/buildmodule/n5/netsee/helloworld_tcp/module/container/
~/buildmodule/n5/netsee/helloworld_tcp/module/helloworld_mod_tcp.cs5
```

Most paths used in generating the new image are paths to the file locations on the host that is building the image. However, the **--entry-point** path is the absolute path to the **entrypoint** file within the container and should be **/usr/bin/entrypoint**, not **~/build-module/n5/netsee/helloworld_tcp/module/container/usr/bin/entrypoint**.

2. Sign the new **.cs5** image using **devcert** and **askeys**:

```
sudo /opt/nfast/bin/csadmin image sign --askeyname ask --devkeyname developerid --devcert
~/ca/developerid_cert.pem --out ~/buildmodule/n5/netsee/helloworld_tcp/module/helloworld_mod_tcp-signed.cs5
~/buildmodule/n5/netsee/helloworld_tcp/module/helloworld_mod_tcp.cs5
```


3. Load the signed container using `csadmin load`:

```
sudo /opt/nfast/bin/csadmin load ~/buildmodule/n5/netsee/helloworld_tcp/module/helloworld_mod_tcp-signed.cs5
```

The output of `csadmin load` contains the UUID of the loaded container. This UUID will be required for starting the container and managing the SSHD keys of the container. The UUID can always be retrieved from the output of `csadmin list`.

4. Load the public key created earlier (`helloworld_tcp_ecdsa_key`) to the container using `csadmin sshd setclient`:

```
sudo /opt/nfast/bin/csadmin sshd keys setclient --uuid fedcba09-8765-4321-1234-567890abcdef --keyfile ~/examplekeys/helloworld_tcp_ecdsa_key.pub
```

5. Enable SSH tunneling on the container:

```
sudo /opt/nfast/bin/csadmin sshd state enable --uuid fedcba09-8765-4321-1234-567890abcdef
```

Example output:

```
FEDC-BA09-8765      SUCCESS
SSHD PORT: 6789
LISTENING ADDRESS: aaaa::aa:aaaa:aaaa:aaaa
```

The output of `sshd state enable` contains the SSHD Port number and the listening address of the container SSHD.

6. Start the container using `csadmin start`:

```
sudo /opt/nfast/bin/csadmin start --uuid fedcba09-8765-4321-1234-567890abcdef
```

`csadmin list` lists the UUIDs of all containers. The IPv6 address of the started container appears in the output of the `csadmin start` command. It can also be found in the output of `csadmin list` and `csadmin stats`.

7. Setup the SSH tunnel on the host:

Run `csadmin sshd state get` and collect the following information:

- Container tunnel address (`ffff::fff:ffff:ffff:ffff`)
- Container port (`8000`)
- SSHD port (`6789`)

- SSHD listening address (`aaaa::aa:aaaa:aaaa:aaaa`)



On nShield Connect the **SSHD listening address** may be an **IPv4** or **IPv6** address

Next, choose a local IP address and port number through which to access the tunnel. Typically localhost is chosen as the local IP address (`127.0.0.1` or `:::1`)

Check the HSM's SSHD public key by running `csadmin sshd keys getserver -u UUID` for comparison against the output from `ssh` on first use, or this could be added to your `known_hosts` file directly.

The SSH tunnel command is formatted as follows:

```
ssh -i ~/examplekeys/helloworld_tcp_ecdsa_key -L LOCAL_IP:LOCAL_PORT:[TUNNEL_ADDRESS%lxcbr0]:CONTAINER_PORT
-f -N -p SSHD_PORT launcher@LISTENING_ADDRESS
```

Using the example data:

```
ssh -i ~/examplekeys/helloworld_tcp_ecdsa_key -L [:::1]:8000:[ffff::fff:ffff:ffff:ffff%lxcbr0]:8000 -f -N -p
6789 launcher@aaaa::aa:aaaa:aaaa:aaaa%nshield0
```



For nShield 5s HSMs, the IPv6 address is link-local and requires the zone index to be appended (typically `%nshield0`). If you are working with a 5c network, replace the IPv6 address with the appropriate nShield 5c network address (IPv4 or IPv6) for your configuration.

8. Run the host-side application.

The host-side application takes three positional arguments, the IPv6 address set up in the forwarding step `:::1`, the port number, and the message to send to the container. The port number used by this example is 8000 by default. The message can be any string of valid characters.

```
~/buildhost/n5/netsee/helloworld_tcp/hostside/helloworld_host_tcp :::1 8000 hello_module
```

Expected Output:

```
nseeContainerMachineIP>:::1
nseeContainerMachinePort=8000
mesg=hello_module
Successful Connection to Socket...
Host>Sending TCP Message-->hello_module
Host>Hello World From HSM!
```

8.7. Run CSEE examples via SSH tunnel

The Classic SEE (CSEE) examples use the SEELib library's SEEJobs functionality for communication with the host (using port **8888** in the container). These examples are identical to examples provided with previous iterations of nShield HSMs and CodeSafe. CSEE applications must be loaded using the **[codesafe]** section of the client-side **hardserver config** file, or by running the **hsc_codesafe** tool directly. Using this configuration support simplifies the deployment of CSEE applications and automates the **csadmin** operations (except for signing) and securely setting up the SSH tunnel.

8.7.1. hello CSEE via automatic configuration

This section describes executing the **hello** CSEE example. The hello example operates functionally identically to the CSEE hello example for Solo XC and Solo+.

The hello example sends a string from the host to the module. The module converts the string to uppercase and returns the string to the host.

1. Generate an input file containing a character string to be sent to the module.

```
echo UPPERCASElowercase > ~/inputfile
```

This input file has both uppercase and lowercase characters.

2. In all CSEE examples, the **network-conf.json** permits only secure communication via the SSH tunnel (and no plaintext communication via **incoming** is allowed by specifying an empty **ports** list), i.e. the **network-conf.json** in the SDK matches the below:

```
cat ~/buildmodule/n5/csee/hello/module/network-conf.json
{
  "incoming": {
    "tcp": {
      "protos": ["ipv6"],
      "ports": []
    }
  },
  "outgoing": {
    "tcp": {
      "protos": ["ipv6"],
      "ports": []
    }
  },
  "ssh_tunnel": {
    "container_port": 8888
  }
}
```

3. Sign the `.cs5` image using `devcert` and `askeys`:

```
sudo /opt/nfast/bin/csadmin image sign --askeyname ask --devkeyname developerid --devcert
~/ca/developerid_cert.pem --out /opt/nfast/custom-seemachines/hello-signed.cs5
~/buildmodule/n5/csee/hello/module/hello.cs5
```

4. Load the signed container using the `[codesafe]` of the client-side `config` file (replacing the `esn` field contents with the actual ESN of the module on which to load the application) and then clearing the module e.g. with `nopclearfail -c -m1` (replacing `1` with the module number in question):

```
[codesafe]
esn=5CB5-41F2-F235
image_file=/opt/nfast/custom-seemachines/hello-signed.cs5
worldid_pubname=hellosee
```

5. Run the host-side application.

The host-side application takes one required positional argument for the input file containing a string to convert to uppercase on the module. Module number is assumed to be `1` by default, use `-m2` to specify module 2 etc. The published object name of the SEE World ID is assumed to be `hellosee` by default (as in the `config` example above); if a different name was used in the `[codesafe]` section of the `config` file, use `-p` parameter to specify it.

```
~/buildhost/n5/csee/hello/hostside/hello ~/inputfile
```

Example output:

```
Worldid: 0x1234abcd
UPPERCASELOWERCASE
```

The module has received the input string `UPPERCASElowercase` and has converted and returned it as a fully uppercase string `UPPERCASELOWERCASE`.

8.7.2. tickets CSEE via automatic configuration

This section describes executing the `tickets` CSEE example. The tickets example operates functionally identically to the tickets example for Solo XC and Solo+. The tickets example serves to demonstrate cryptographic functionality by encrypting and having the module decrypt a user-provided string.

1. Generate a simple RSA key to encrypt with:

```
sudo /opt/nfast/bin/generatekey --module=1 simple type=RSA pubexp=3 ident=encryptionkeytickets
plainname=encryptionkeytickets protect=module nvram=no size=2048
```

2. Sign the `.cs5` image using `devcert` and `askeys`:

```
sudo /opt/nfast/bin/csadmin image sign --askeyname ask --devkeyname developerid --devcert
~/ca/developerid_cert.pem --out /opt/nfast/custom-seemachines/seetickets-signed.cs5
~/buildmodule/n5/csee/tickets/module/seetickets.cs5
```

3. Load the signed container using the `[codesafe]` of the client-side `config` file (replacing the `esn` field contents with the actual ESN of the module on which to load the application) and then clearing the module e.g. with `nopclearfail -c -m1` (replacing `1` with the module number in question):

```
[codesafe]
esn=5CB5-41F2-F235
image_file=/opt/nfast/custom-seemachines/seetickets-signed.cs5
worldid_pubname=ticketsee
```

4. Run the host-side application.

The host-side application accepts the encryption key created earlier as an optional argument (`--key`). Module number is assumed to be `1` by default, use `-m2` to specify module 2 etc. The published object name of the SEE World ID is assumed to be `ticketsee` by default (as in the `config` example above); if a different name was used in the `[codesafe]` section of the `config` file, use `-p` parameter to specify it.

```
~/buildhost/n5/csee/tickets/hostside/hosttickets --key simple,encryptionkeytickets
```

5. When prompted, enter a string to encrypt (for example, `testencryption`) and press **Return**:

```
Enter string to be encrypted (256 characters maximum): testencryption
```

The host encrypts the message then the module decrypts it and returns it in plain text format.

Example output:

```
HostSide> Loading security world key (simple,encryptionkeytickets)
HostSide> Creating World: init status was 0 (OK)
HostSide> Sending ticket for private RSA key to module
HostSide> Generating AES session key and creating blob under public RSA key
HostSide> Sending key blob to module
HostSide> Sending cipher-text to module
HostSide> decrypted cipher text received from SEE machine:
```

```
"testencryption"
HostSide> Thank you for watching. The end.
```

8.7.3. benchmark CSEE via automatic configuration

This section describes executing the **benchmark** CSEE example. The benchmark example operates functionally identically to the benchmark example for Solo XC and Solo+. The benchmark example will transact asynchronously with the module running multiple threads processing transactions. The benchmark example will output transactions/second data every second.

1. Generate a simple key for signing a ticket in the bm-machine on the module:

```
sudo /opt/nfast/bin/generatekey --module=1 simple type=RSA pubexp=3 ident=signingkeybenchmark
plainname=signingkeybenchmark protect=module nvram=no size=2048
```

2. Sign the **.cs5** image using **devcert** and **askeys**:

```
sudo /opt/nfast/bin/csadmin image sign --askeyname ask --devkeyname developerid --devcert
~/ca/developerid_cert.pem --out /opt/nfast/custom-seemachines/bm-machine-signed.cs5
~/buildmodule/n5/csee/benchmark/module/bm-machine.cs5
```

3. Load the signed container using the **[codesafe]** of the client-side **config** file (replacing the **esn** field contents with the actual ESN of the module on which to load the application) and then clearing the module e.g. with **nopclearfail -c -m1** (replacing **1** with the module number in question):

```
[codesafe]
esn=5CB5-41F2-F235
image_file=/opt/nfast/custom-seemachines/bm-machine-signed.cs5
worldid_pubname=bmsee
```

4. Run the host-side application.

The host-side application takes two positional arguments: the appname and the key name of the signing key created earlier. Module number is assumed to be **1** by default, use **-m2** to specify module 2 etc. The published object name of the SEE World ID is assumed to be **bmsee** by default (as in the **config** example above); if a different name was used in the **[codesafe]** section of the **config** file, use **-p** parameter to specify it.

```
~/buildhost/n5/csee/benchmark/hostside/bm-test simple signingkeybenchmark
```

Example output:

```
Worldid: 0x1234abcd
1 759 759.00
2 1522 761.00
3 2361 787.00
4 3324 831.00
5 4238 847.60
6 5124 854.00
7 5948 849.71
8 6723 840.38
9 7579 842.11
10 8408 840.80
```

9. Build and sign example SEE machines on Windows

9.1. Prerequisites

- Visual Studio 2022 buildtools
- CMAKE version 3.9 or newer
- Ninja build system latest version
- Visual Studio 2022 workload-vctools

9.2. Building Windows CodeSafe C, CSEE, and NETSEE examples

1. Start the Developer Command Prompt for VS 2022 as Administrator from the **Start** menu.
2. Navigate to the following directory:

```
cd "c:\Program Files (x86)\Microsoft Visual Studio\2022\BuildTools\Common7\Tools"
```

3. Install the MSVC C and C++ compiler **cl.exe**.
4. Execute **VsDevCmd.bat**:

```
VsDevCmd.bat
```

5. Run **cl**:

```
cl
```

6. Because the default is 32bit mode, the version displayed will show x86. Change to 64bit **cl** Compiler:

```
cd "c:\Program Files (x86)\Microsoft Visual Studio\2022\BuildTools\VC\Auxiliary\Build"
```

7. Execute **vcvars64.bat**:

```
vcvars64.bat
```


8. Run **cl** and verify that the x64 version is displayed:

```
cl
```

you can build the following examples in the same VS2022 Command window:

9.2.1. Host-side examples

```
c:\>mkdir examples\host

c:\>cd c:\examples\host\

c:\examples\host>cmake -G Ninja -DCMAKE_C_COMPILER=cl -DCMAKE_CXX_COMPILER=cl "c:\Program
Files\NCipher\nfast\c\csd5\examples"

c:\examples\host>ninja
```

9.2.2. Module-side examples

```
c:\>mkdir examples\module

c:\>cd c:\examples\module\

c:\examples\module>cmake -G "Ninja" -DCMAKE_TOOLCHAIN_FILE="c:\Program Files\NCipher\nfast\c\csd5\cmake\codesafe-
toolchain-nshield5-csee.cmake" "c:\Program Files\NCipher\nfast\c\csd5\examples"

c:\examples\module>ninja
```

9.3. CS5 images for Python examples

Build the following images in the VS2022 Command window configured in [Building Windows CodeSafe C, CSEE, and NETSEE examples](#). You do not need to build host-side and module-side Python examples separately. They are both built into **examples\python\n5\netsee\<example>\.**

```
c:\>mkdir examples\python

c:\>cd c:\examples\python\

c:\examples\python>cmake -G "Ninja" "c:\Program Files\NCipher\nfast\python3\csd5\examples"

c:\examples\python>ninja
```

For example:

```
c:\examples\python\n5\netsee\tickets>dir
Volume in drive C is OS
```

```
Volume Serial Number is 582A-CFB6 Directory of c:\examples\python\n5\netsee\tickets 03/21/2023 12:32 PM <DIR>
.
03/21/2023 12:32 PM <DIR> ..
03/21/2023 12:32 PM <DIR> hostside
03/21/2023 12:32 PM <DIR> module
                0 File(s)                0 bytes
                4 Dir(s) 906,165,829,632 bytes free
```

9.4. Sign CodeSafe images



Signing CodeSafe Images requires a Security World and Operator Card Set (OCS).

1. Insert the OCS card.
2. Create a certificate signing request (CSR) that should be sent to Entrust to be signed:

```
c:\ca_ids>csadmin ids create --keyname testdeveloperkey --x509cname developer.entrust.com --x509country US
--x509province FL --x509locality Shakopee --x509org Entrust --x509orgunit "Entrust CodeSafe"
Generate key 'testdeveloperkey' ...

Loading 'TestOCS':
Module 1: 0 cards of 1 read
Module 1 slot 0: empty
Card reading complete.

OK
Generate a CSR in 'testdeveloperkey.csr' ...
OK
Created CSR file 'testdeveloperkey.csr'. Please send it to Entrust Support
```



The developer ID creation in this example was done with **TestOCS**, quorum of 1/1. Exact output may vary slightly with different OCS quorums.

3. Send the resulting CSR to customer support to be signed by Entrust. You must obtain the signed developer ID certificate in order to sign and load an application.

For more detailed information on Developer IDs and CSRs, see [Sign and deploy CodeSafe 5 SDK apps using csadmin](#).

4. Create the ASK on the HSM (the name of the key in this example is **test-ask**). The following example specifies the key to be protected by the module. However, end users are encouraged to protect the key with an OCS:

```
c:\ca_ids>C:\Program Files\Cipher\fast\bin\generatekey.exe --module=1 simple type=ECDSA curve=NISTP521
ident=test-ask plainname=test-ask
protect: Protected by? (token, module) [token] > module
nvrn: Blob in NVRAM (needs ACS)? (yes/no) [no] >
key generation parameters:
operation    Operation to perform    generate
```

```

application  Application      simple
protect      Protected by    module
verify       Verify security of key  yes
type         Key type      ECDSA
ident        Key identifier  test-ask
plainname    Key name       test-ask
nvram        Blob in NVRAM (needs ACS) no
curve        Elliptic curve  NISTP521
Key successfully generated.
Path to key: C:\ProgramData\nCipher\Key Management Data\local\key_simple_test-ask

```

5. Confirm that the keys were created in the previous step:

```

c:\ca_ids>nfkminfo -k
Key list - 2 keys
  AppName simple      Ident test-ask
  AppName simple      Ident testdeveloperkey

```

6. Sign the **netsee\tickets** example. You need the signed **cert.pem** from customer support for this step and the OCS card must be inserted for signing.

```

c:\examples\module\n5\netsee\tickets_netsee\module>csadmin image sign --askeyname test-ask --devkeyname
testdeveloperkey --devcert c:\ca_ids\testdeveloperid_cert.pem --out seetickets_netsee-signed-with-hsm.cs5
seetickets_netsee.cs5
INFO: Reading CS5 file contents...
INFO: Getting key handle from HSM...

INFO: Signing the Application Signing Key...
INFO: hashing contents using 'SHA512Hash'
INFO: Obtaining public key data from HSM...
INFO: Storing public key data on CS5 file...
INFO: Getting key handle from HSM...
INFO: Requesting signature from HSM...
INFO: Saving CS5 file to disk...
INFO: file 'seetickets_netsee.cs5' was signed successfully!

Directory of c:\examples\module\n5\netsee\tickets_netsee\module

02/16/2023  03:53 PM          27,167,860 seetickets_netsee-signed-with-hsm.cs5
             1 File(s)          27,167,860 bytes
             0 Dir(s)  775,613,321,216 bytes free

```

7. Where applicable, sign the CodeSafe image with non-ASK keys, for example:

```

c:\examples\module\n5\netsee\tickets_netsee\module> csadmin image signextra --appname seeinteg --key
seeintkeyname --out seetickets_netsee-signed-with-hsm-extra.cs5 seetickets_netsee-signed-with-hsm.cs5
INFO: file 'seetickets_netsee-signed-with-hsm.cs5' was signed successfully!

```

8. Install the developer ID certificate chain from Entrust using **csadmin ids add**:

```

csadmin ids add entrust_developerid_cert_chain.pem
FEDC-BA09-8765      SUCCESS

csadmin ids list
FEDC-BA09-8765      SUCCESS
Certificates:

```

```
{'serialNumber': '1', 'subject': 'Common Name: developer.entrust.com, Organizational Unit: Entrust
CodeSafe, Organization: Entrust, Locality: Shakopee, State/Province: Minnesota, Country: US', 'keyid':
'abcdef12345678900987654321fedcbaabcdef12', 'authKeyid': '0987654321fedcbaabcdef123456789009876543',
'notBefore': '2023-01-01 12:34:56+00:00', 'notAfter': '2024-01-01 12:34:56+00:00'}
{'serialNumber': '2', 'subject': 'Common Name: developer.entrust.com, Organizational Unit: Entrust
CodeSafe, Organization: Entrust, Locality: Shakopee, State/Province: Minnesota, Country: US', 'keyid':
'1234567890abcdeffedcba098765432112345678', 'authKeyid': 'fedcba09876543211234567890abcdeffedca098',
'notBefore': '2023-01-01 12:34:56+00:00', 'notAfter': '2024-01-01 12:34:56+00:00'}
```

9. Execute `netsee\tickets`:

```
c:\examples\module\n5\netsee\tickets_netsee\module>csadmin load seetickets_netsee-signed-with-hsm.cs5
FEDC-BA09-8765: Uploading seetickets_netsee-signed-with-hsm.cs5
FEDC-BA09-8765: creating machine
FEDC-BA09-8765          SUCCESS
UUID: fedcba09-8765-4321-1234-567890abcdef

c:\examples\module\n5\netsee\tickets_netsee\module>cd c:\examples\host\n5\netsee\tickets_netsee\hostside

c:\examples\host\n5\netsee\tickets_netsee\hostside>nopclearfail -a0
Module 1, command ClearUnitEx: OK

c:\examples\host\n5\netsee\tickets_netsee\hostside>csadmin start -u fedcba09-8765-4321-1234-567890abcdef
FEDC-BA09-8765          SUCCESS
IP ADDRESS: ffff::fff:ffff:ffff:ffff

c:\examples\host\n5\netsee\tickets_netsee\hostside>csadmin list
FEDC-BA09-8765
UUID                                State    Name                                IP Address
-----
fedcba09-8765-4321-1234-567890abcdef  RUNNING seetickets_netsee  ffff::fff:ffff:ffff:ffff

c:\examples\host\n5\netsee\tickets_netsee\hostside>hosttickets_netsee.exe -p 8000 -U fedcba09-8765-4321-
1234-567890abcdef -i ffff::fff:ffff:ffff:ffff%10 -c
c:\examples\module\n5\netsee\tickets_netsee\module\seetickets_netsee-signed-with-hsm.cs5
WSAStartup() Success.
HostSide>Enter string to be encrypted (8 characters maximum): hello
HostSide>Reading Identities from container
HostSide>Generating RSA keypair
HostSide>Creating World: init status was 0 (OK)
HostSide>Sending ticket for private RSA key to module
HostSide>Sending key blob to module
HostSide>Sending cipher-text to module
HostSide>decrypted cipher text received from SEE machine:
"hello"
HostSide>Thank you for watching. The end.
```

10. Build and run Java examples

The following Java examples are included:

- [BenchMark5](#)
- [Echo5](#)
- [HelloWorld5](#)
- [HostTickets5](#)

10.1. Prerequisites

The following versions of Java have been tested to work with, and are supported by, your nShield Security World Software:

- Java8 (or Java 1.8x)
- Java11
- Java17
- Java21

Ensure that Java is installed before you install the Security World software. The Java executable must be on your system path.

If you can do so, please use the latest Java version currently supported by Entrust that is compatible with your requirements. Java versions before those shown are no longer supported.

10.2. The Java interface

The Java interface works with the same SEE machines as the C compatibility interface, see [Compatibility layer for legacy SEE machines](#). These examples work with the SEE machines built in [Build and sign example SEE machines on Linux](#) and [Build and sign example SEE machines on Windows](#).

CodeSafe5 uses SEEWORLD5 instead of SEEWORLD and SEE5CONNECTION instead of EASYCONNECTION. The SEE5CONNECTION constructor takes the same arguments as the EASYCONNECTION constructor. The only difference in behavior between SEE5CONNECTION and EASYCONNECTION is the handling of SEEJOB commands: if a SEE5CONNECTION has an open socket, SEEJOB commands are diverted to the socket. This is the same as the legacy SEE machine interface. SEE5CONNECTION can only route to a single module. World ID is ignored.



If you are supplying a `SEE5Connection` to the `SEE5World` constructor, do not open the socket. The `SEE5World` constructor opens the socket and it will fail if the socket is already open.

The interface supports multi-threaded access to the SEE machine with asynchronous command processing. There is no timeout on commands, so if no reply is received, threads could be blocked indefinitely.

10.3. Build the examples

The Java example files are in the `nCipherKM-See-Examples.jar` in `opt/nfast/java/examples` (**Linux**) or `%NFAST_HOME%\java\examples` (**Windows**).

Extract and compile the examples:

Linux

```
cd /opt/nfast/java/examples
jar xf nCipherKM-SEE-Examples.jar
jar xf ../classes/nCipherKM-jhsee.jar
javac -cp /opt/nfast/java/classes/nCipherKM.jar com/ncipher/see/hostside/*.java
javac -cp ./opt/nfast/java/classes/nCipherKM.jar
com/ncipher/see/hostside/examples/benchmark5/BenchMark5.java
javac -cp ./opt/nfast/java/classes/nCipherKM.jar com/ncipher/see/hostside/examples/echo5/Echo5.java
javac -cp ./opt/nfast/java/classes/nCipherKM.jar
com/ncipher/see/hostside/examples/helloworld5/HelloWorld5.java
javac -cp ./opt/nfast/java/classes/nCipherKM.jar
com/ncipher/see/hostside/examples/hosttickets5/HostTickets5.java
```

Windows

```
cd %NFAST_HOME%\java\examples
jar xf nCipherKM-SEE-Examples.jar
jar xf ../classes\nCipherKM-jhsee.jar
javac -cp "%NFAST_HOME%\java\classes\nCipherKM.jar com\ncipher\see\hostside\*.java"
javac -cp "%NFAST_HOME%\java\classes\nCipherKM.jar ^
com\ncipher\see\hostside\examples\benchmark5\BenchMark5.java"
javac -cp "%NFAST_HOME%\java\classes\nCipherKM.jar ^
com\ncipher\see\hostside\examples\echo5\Echo5.java"
javac -cp "%NFAST_HOME%\java\classes\nCipherKM.jar ^
com\ncipher\see\hostside\examples\helloworld5\HelloWorld5.java"
javac -cp "%NFAST_HOME%\java\classes\nCipherKM.jar ^
com\ncipher\see\hostside\examples\hosttickets5\HostTickets5.java"
```

10.4. Run the examples

All the examples take the following arguments:

- **ipAddress**: The IPv6 address of the container. This can be obtained by running `csadmin list --esn <module-esn>`, assuming that the SEE machine has been started.

- **UUID**: This can be obtained by running `csadmin list`.
- **see-signing-key-hash** (without spaces): This can be obtained by running `npkgtool inspect` with the signed SEE machine.

The key hash is on the `.data.hash=` line.

For example:

```
$ npkgtool inspect hello-signed.cs5
....
NpkgRecord.item.tag= KeyData
    .value.keyname= ask
    .use= FileSignature
    .hashid.mech= SHA1Hash
    .data.hash= xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx xxxxxxxx
....
```

All examples can be run with the following help options:

- **-h, --help**: Displays the help message.
- **-v, --version**: Displays the version number of this program.
- **-u, --usage**: Displays a brief usage summary.

Before running the examples, ensure that you are in the `examples` directory:

Linux

```
cd /opt/nfast/java/examples
```

Windows

```
cd %NFAST_HOME%\java\examples
```

10.4.1. BenchMark5

BenchMark5 is a simple demonstration of a Java hostside app for benchmarks.

Linux

```
java cp ../opt/nfast/java/classes/nCipherKM.jar com.ncipher.see.hostside.examples.benchmark5.BenchMark5
[options] <ipAddress> <see-signing-key-hash> <key-app>
```

Windows

```
java cp "%NFAST_HOME%\java\classes\nCipherKM.jar" ^
com\ncipher\see\hostside\examples\benchmark5\BenchMark5 [options] <ipAddress> <UUID> <see-signing-key-hash>
<key-app>"
```

Options:

- **-m, --module=MODULE**: Use module MODULE.
Default: 1
- **-s, --slot=SLOT**: Use slot SLOT for operator cards.
Default: 0
- **-t, --threads=THREADS**: Use THREADS threads.
Default: 32
- **-i, --iterations=ITERATIONS**: Each thread will perform ITERATIONS iterations.
Default: 100
- **-l, --logfile=LOGFILE**: Record public key and timestamps in file LOGFILE.

Arguments:

- **key-app**: The key to be used to encrypt the data. This must be an RSA key, for example **simple rsa2k**. See [generatekey](#) for more information.

For example:

```
$ java cp ./opt/nfast/java/classes/nCipherKM.jar com.ncipher.see.hostside.examples.benchmark5.BenchMark5 -i 10
xxxx::xxx:xxxx:xxxx:xxxx%nshield0 xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxxx xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
simple rsa2k
Generating 320 Timestamps Using 32 threads
Sending ticket...
Threads started...
Finished!
```

10.4.2. Echo5

Echo5 is a simple demonstration of a Java hostside app for performance testing.

Linux

```
java cp ./opt/nfast/java/classes/nCipherKM.jar com.ncipher.see.hostside.examples.echo5.Echo5 [options]
<ipAddress> <UUID> <see-signing-key-hash>
```

Windows

```
java cp "%NFAST_HOME%\java\classes\nCipherKM.jar ^
com\ncipher\see\hostside\examples\echo5\Echo5 [options] <ipAddress> <UUID> <see-signing-key-hash>
```

Options:

- **-m, --module=MODULE**: Use module MODULE.
Default: 1

- **-t, --threads=THREADS**: Use THREADS threads.
Default: 32
- **-p, --payload=PAYLOAD**: Send PAYLOAD bytes.
Default: 32
- **-i, --iterations=ITERATIONS**: Each thread will perform ITERATIONS iterations.
Default: 100
- **-e, --verify**: Verify that the returned value matches the value sent.

For example:

```
$ java cp ./opt/nfast/java/classes/nCipherKM.jar com.ncipher.see.hostside.examples.echo5.Echo5 -i 10
xxxx::xxx:xxx:xxx:xxx%nshield0 xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
Threads = 32 Payload = 32 bytes Iterations = 10 Verify replies = OFF
320 jobs in 0.04 seconds = 9006.18 jobs/Second, 288198 bytes/second
```

10.4.3. HelloWorld5

HelloWorld5 is a simple demonstration of a Java hostside app talking to a C SEE machine. It takes the text from an `<inputFile>` and outputs it with all the lower-case text converted to upper-case text.



The `HelloWorld5.java` example is not intended for use as the basis for real world applications.

Linux

```
java cp ./opt/nfast/java/classes/nCipherKM.jar com.ncipher.see.hostside.examples.helloworld5.HelloWorld5
[options] <inputFile> <ipAddress> <UUID> <see-signing-key-hash>
```

Windows

```
java cp "%NFAST_HOME%\java\classes\nCipherKM.jar ^
com\ncipher\see\hostside\examples\helloworld5\HelloWorld5 [options] <inputFile> <ipAddress> <UUID> <see-
signing-key-hash>"
```

Options:

- **-m, --module=MODULE**: Use module MODULE.
Default: 1

For example:

```
$ cat /tmp/testfile.txt
lowercase
$ java cp ./opt/nfast/java/classes/nCipherKM.jar com.ncipher.see.hostside.examples.helloworld5.HelloWorld5
/tmp/testfile.txt xxxx::xxx:xxx:xxx:xxx%nshield0 xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx
```

```
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
LOWERCASE
```

10.4.4. HostTickets5

HostTickets5 is a simple demonstration of a Java hostside app using tickets.

Linux

```
java cp ./opt/nfast/java/classes/nCipherKM.jar com.ncipher.see.hostside.examples.hosttickets5.HostTickets5
[options] <ipAddress> <UUID> <signing-key-hash>
```

Windows

```
java cp "%NFAST_HOME%\java\classes\nCipherKM.jar ^
com\ncipher\see\hostside\examples\hosttickets5\HostTickets5 [options] <ipAddress> <UUID> <see-signing-key-
hash>"
```

Options:

- **-m, --module=MODULE**: Use module MODULE.

Default: 1

- **-s, --string=STRING**: String to be encrypted.

If you do not use this option, you will be prompted for a string when you execute the command.

for example:

```
$ java -cp ./opt/nfast/java/classes/nCipherKM.jar com.ncipher.see.hostside.examples.hosttickets5.HostTickets5
-s encryptme xxxx:xxx:xxxx:xxxx:xxxx%nshield0 xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
String to be encrypted = encryptme
Sending ticket...
Sending blobbed key...
Sending encrypted text...
Decrypted text = encryptme
```

11. Debug CodeSafe 5 SEE machines

11.1. SEE machine logging

SEE machine logs capture any stdout and stderr from the container. This can be used to capture log messages from the IPC daemon or SEELib library, or from the SEE machine's own logging framework.

If [automatic configuration](#) is used via `[codesafe]` section in `config` or via the `hsc_codesafe`, logging in the SEE machine is enabled by default (unless explicitly disabled), in which case retrieving and clearing the logs are the only applicable commands below.

The following SEE logging-related commands are supported by the `csadmin` utility.

11.1.1. config log set enabled

The `config log set enabled` command should be issued before the `start` command. It uses the following format:

```
/opt/nfast/bin/csadmin config set log enabled -u <SEE-machine-UUID> --esn <host-ESN>
```

- `<SEE-machine-UUID>` is the UUID of the SEE machine created by the load command.
- `<host-ESN>` is the ESN of the HSM hosting the SEE Machine.

For example:

```
/opt/nfast/bin/csadmin config set log enabled -u fedcba09-8765-4321-1234-567890abcdef --esn FEDC-BA09-8765
```

When successful, the command returns with no error.

11.1.2. config log set disabled

The `config log set disabled` command should be issued while the SEE machine is not running. It uses the following format:

```
/opt/nfast/bin/csadmin config set log disabled -u <SEE-machine-UUID> --esn <host-ESN>
```

- `<SEE-machine-UUID>` is the UUID of the SEE machine created by the load command.
- `<host-ESN>` is the ESN of the HSM hosting the SEE Machine.

For example:

```
/opt/nfast/bin/csadmin config set log disabled -u fedcba09-8765-4321-1234-567890abcdef --esn FEDC-BA09-8765
```

When successful, the command returns with no error.

11.1.3. log get

The **get** command returns the current SEE log contents, if any. It uses the following format:

```
/opt/nfast/bin/csadmin log get -u <SEE-machine-UUID>
```

<SEE-machine-UUID> is the UUID of the SEE machine created by the load command.

For example:

```
/opt/nfast/bin/csadmin log get -u fedcba09-8765-4321-1234-567890abcdef
FEDC-BA09-8765      SUCCESS
Success: Started ipcdemon
```

11.1.4. log clear

The **clear** command deletes the current SEE log file if present. It uses the following format:

```
/opt/nfast/bin/csadmin log clear -u <SEE-machine-UUID>
```

<SEE-machine-UUID> is the UUID of the SEE machine created by the load command.

For example:

```
/opt/nfast/bin/csadmin log clear -u fedcba09-8765-4321-1234-567890abcdef
FEDC-BA09-8765      SUCCESS
log: log cleared
```

11.2. Crash Reporter

If the CodeSafe 5 application links against the **seelib.a** library, an in-process crash reporter will be registered for various termination and crash signals before **main()**.

If the application receives one of the handled signals, a crash report will be written to the SEE log, like the below:

```
SEE MACHINE CRASH: SIGSEGV (Invalid memory reference)
  Sending process PID: 0
  Sending process UID: 0
  Fault address: 0xcafecafecafecafe
  SEGV_MAPERR: Address not mapped to object.
  crashing.c: 298 -- -- some_crashing_function
  main.c: 56 -- -- main
Segmentation fault
```

In order to obtain a useful crash backtrace, the SEE machine should be built with debugging symbols at least at **-g1** level and not have the symbols stripped from the binary.

12. Uninstall the CodeSafe 5 SDK



Do not uninstall Security World or CodeSafe 5 software unless you are certain it is no longer required or you are going to upgrade it.

If you are using CodeSafe 5 with an nShield 5s HSM, you must back up its `sshadmin` keys by running `hsmadmin keys backup` before you uninstall Security World or CodeSafe 5.

The uninstaller only removes files that were created during the installation. To remove key data or Security World data, navigate to the installation directory and delete the files in the `%NFAST_KMDATA%` folder.

If you intend to remove your Security World before uninstalling the Security World Software, Entrust recommends that you erase the OCS before you erase the Security World or uninstall the Security World Software. Except where Remote Administration cards are used, after you have erased a Security World, you can no longer erase any cards that belonged to it.

1. Log in to the host computer as Administrator or as a user with local administrator rights.
2. Run the following command to erase the OCS:

```
createocs -m# -s0 --erase
```

Where `#` is the module number.

3. Uninstall the Security World and CodeSafe software:

- **Linux:**

Run the following command:

```
/opt/nfast/sbin/install -u
```

- **Windows:**

1. Navigate to the Windows Control Panel, and select **Programs and Features**.
2. Select the Security World Software entry, then select **Uninstall** to remove the software.

If required, you can safely remove the nShield module after shutting down all connected hardware.

13. Port existing CodeSafe application to CodeSafe 5

Follow the steps in this chapter if you need to port an existing SEE machine to run on CodeSafe 5.

This chapter assumes the perspective of a CodeSafe application developer.

CodeSafe users using third-party CodeSafe applications for HSM models prior to nShield 5 should contact the developer of those applications to obtain a CodeSafe 5 version of the application. Ensure that the third-party CodeSafe developer is a trusted party, and can provide a signed CodeSafe 5 application and associated developer ID certificate issued by Entrust.

Examples of Classic SEE "CSEE" machines that have been ported to CodeSafe 5 can be found in [Build and sign example SEE machines on Linux](#). These are examples from previous HSM models that have been modified to run with CodeSafe 5. In all other ways, these examples are identical to examples provided with previous iterations of nShield HSMs and CodeSafe.



It is assumed that an ASK and developer ID key have already been generated, and that required certificates have already been obtained from Entrust and installed into the target HSM.

13.1. Communication with the host

Legacy CodeSafe transacted data between host application and module SEE machines by sending SEEJobs via the hardserver to the HSM's nCore API service, onto the CodeSafe application, and back again. TCP communication with the host was supported with a net-working emulation layer on top of this protocol.

CodeSafe 5 continues to support SEEJobs via the hardserver, but this protocol is now implemented via a securely negotiated SSH tunnel automatically set up between the client hardserver and the CodeSafe application directly without the nCore API service being required to forward the jobs.

Additionally, the TCP network emulation layer (provided by `see-sock-serv` and related configuration support for BSDSEE/GLIBSEE applications) on top of the SEEJobs protocol has been removed and replaced with a first-class networking implementation which supports TCP and UDP between the host and the CodeSafe application.



The module-side SEE machine must be rebuilt and re-signed to function

on CodeSafe 5 (CodeSafe applications from previous HSM models cannot run on nShield 5). The host-side client application communicating with the SEE machine may or may not require updates depending on how it interacts with the SEE machine, but details for loading and running the CodeSafe application from the client differ from previous HSM models and will need to be changed.

13.2. SEELib library

The module-side SEELib library behaves the same as before for both communication with the nCore API service on the HSM to execute `M_Command` commands and also for communication with the host via SEEJobs. Assuming the use of the default port of `8888` for SEEJobs, no source changes should be required, though it will be necessary to include a `network-conf.json` as per the CSEE examples to permit port `8888` as the `ssh_tunnel` port (and not to allow `incoming` plaintext access to this port).

Host-side applications continue to send SEEJobs (i.e. `Cmd_SEEJob` and `Cmd_FastSEEJob` commands) via an nCore connection to the hardserver, using the SEE World ID as the identifier for the SEE machine.

13.3. Deployment differences

See [Automatic Configuration of CodeSafe 5 Applications](#) for information about automatic loading of CodeSafe 5 applications using the `[codesafe]` section of the `config` file or using the `hsc_codesafe` tool. The `[codesafe]` section replaces the `[load_seemachine]` section used by previous HSM models.



The "CodeSafe Direct" feature of loading a SEE machine from the nShield Connect `config` file is not supported by nShield 5, but the new `[codesafe]` section can be used to automatically load a SEE machine from a client hardserver `config` file instead. If using this with nShield 5, one client of the nShield 5c should have that `[codesafe]` configuration as only one CodeSafe application may be run at a time.

See the examples in [Build and sign example SEE machines on Linux](#) for information about running both TCP/UDP applications and CSEE applications with CodeSafe 5.

The NetSEE examples documentation explains how to configure networking; this replaces the network emulation that legacy `see-sock-serv` and related configuration provided.

The CSEE examples documentation show how to deploy using published objects for the

SEE World ID with the SEE machine automatically loaded via the `config` file, which is the simplest way to deploy, and was also a supported approach for interacting with SEE machines in legacy CodeSafe. Applications that were using published objects will require the fewest updates.

If the SEE World ID was previously loaded directly by the host-side application using `Cmd_CreateSEEWorId` within a hardserver connection, that should now be replaced with `Cmd_CreateSEEConnection`. If it was loaded using the `seeworld_auth_setup()` or `seeworld_setup()` helper functions from the `seeworld.h` / `seeworld.c` example utility code, `seeworld_connect()` should now be used instead. If using the `SEEWorId` class to load the SEE World ID in a Java application, `SEEWorId5` should now be used instead.



A SEE World ID is required if communicating with the SEE machine via SEEJobs as it is the handle for those jobs, but it may also be required even when not using SEEJobs if the SEE machine talks (locally) to the nCore API service on the HSM (for example to transact cryptographic `M_Command` commands such as signing or decryption) as the act of doing the `Cmd_CreateSEEConnection` from the host creates the permission for the CodeSafe application to use the nCore API service.

13.4. User Data

CodeSafe 5 does not retain the concept of `UserData` as a separate cpio or SAR file input alongside the CodeSafe application.

A developer can instead include any files, using any directory structure, in the container image that is installed in the HSM.

14. Supporting legacy CodeSafe Direct

CodeSafe Direct is no longer available in CodeSafe 5. The following sections describe the usage of legacy CodeSafe Direct and how similar functionality is accomplished via CodeSafe 5.

14.1. Legacy CodeSafe Direct

Originally, the application would connect to the HSM through the Security World hardserver. With legacy CodeSafe Direct, the nShield Connect could be configured to receive direct socket connections to the SEE machine via `see-sock-serv`, removing the need for a client machine. You could do this by specifying `postload_prog` and `postload_args` in the `load_seemachine` section of the nShield Connect hardserver configuration file, located in `NFAST_KMDATA/hsm-<ESN>`, where `<ESN>` is the Electronic Serial Number of the HSM.

14.2. CodeSafe 5

The CodeSafe 5 modern architectural approach provides a container which has an IPC daemon (UNIX domain socket) that is used to send and receive nCore API commands and replies. The communication between the host application and CodeSafe 5 container is provided by a secure SSH daemon making use of port forwarding.

The `Cmd_SEEJob` nCore API command is no longer supported by the nCoreAPI service. Instead, the command is now requested directly from the client application on the host to the SEE machine using a direct TCP connection. A support library is needed to support this new connection, and this is part of the compatibility layer.

Containers listening on a specific port via the secure channel is a 'CodeSafe Direct' replacement.

There are cli commands using the 'csadmin' utility that can establish the secure SSHD port forwarding on the host client machine. The `cs5-port-monitor` will validate and then forward the ports specified in `network-conf.json`. See [Build and sign example SEE machines on Linux](#) for examples of using an SSH tunnel to communicate between the client and SEE machine directly through a TCP/IPv6 network connection to the container. Containers can be configured to listen to ports using the `network-conf.json` file.

15. SEE API documentation

SEELib is an API that enables an SEE machine to both execute nCore API commands and to accept messages from the host machine via the SEEJobs protocol. It is supported both in CodeSafe 5 and in CodeSafe for previous HSM models.



The **SEELib** API is provided as a library **seelib.a** that can be found in the rootfs after install. Its install location is **/opt/nfast/c/csd5/lib-ppc64-linux-musl/seelib.a** on Linux.

15.1. SEELib functions

15.1.1. SEELib_init

```
extern void SEELib_init(void);
```

This function initializes the **SEELib** library.



This function does not return on error.

15.1.2. SEELib_ReadUserData

```
extern int SEELib_ReadUserData ( M_Word offset, unsigned char *buf, M_Word len );
```

This function reads selected bytes from the **UserData** block, starting at **offset** bytes in and continuing for **len** bytes. It returns an **M_Status** value.

As the concept of a separate **UserData** input does not exist in CodeSafe 5, for backwards compatibility this function is supported as reading a file located inside the container (**/etc/codesafe.userdata**) which must be added at that path when the container image is constructed.

15.1.3. SEELib_ReleaseUserData

```
extern void SEELib_ReleaseUserData(void);
```

In CodeSafe 5 this function does not do anything. It is only present for backwards compatibility.

15.1.4. SEELib_InitComplete

```
extern void SEELib_InitComplete( M_Word status );
```

In CodeSafe 5 this function does not do anything. It is only present for backwards compatibility.

15.1.5. SEELib_StartTransactListener

```
extern void SEELib_StartTransactListener(void);
```

This function starts the thread that listens for `SEELib_Transact` calls and dispatches them. This function must be called before any use is made of `SEELib_Transact`.

15.1.6. SEELib_Transact

```
extern int SEELib_Transact(struct M_Command *cmd, struct M_Reply *buf);
```

This function marshals a command, submits it, waits for the response, and unmarshals it into a reply structure.

15.1.7. SEELib_MarshalSendCommand

```
extern int SEELib_MarshalSendCommand(M_Command *cmd);
```

This function marshals a command and places it on the input queue for processing by the nShield core.

The command takes a reference to an `M_Command` structure, as described in the *nCore CodeSafe API Documentation*.

The SEE machine can submit any of the nCore API commands listed in the *Basic commands* and *Key-Management commands* sections of the *nCore CodeSafe API Documentation* except:

- `RetryFailedModule`
- `GetWhichModule`
- `MergeKeyIDs`.

If the SEE machine attempts to submit one of these commands, the nShield core returns a response with the status code **NotAvailable**.

The **SEELib_MarshalSendCommand** function returns an **M_Status** value. This value is **OK** if the command was marshalled and transferred to the nShield core correctly.



Do not mix calls to **SEE_Transact()** and **SEELib_MarshalSendCommand()** and **SEELib_GetUnmarshalResponse()**, because the replies may be misdirected.

15.1.8. SEELib_GetUnmarshalResponse

```
extern int SEELib_GetUnmarshalResponse(M_Reply *buf);
```

If there is a reply in the input queue for this SEE world, this function returns the first job in the queue. Otherwise, it blocks and waits for the nShield core to return a job.

On return, **M_Reply** contains the unmarshalled reply.

The **SEELib_GetUnmarshalResponse** function returns an **M_Status** value. This value is **OK** if the reply was unmarshalled successfully. The return of this value does not necessarily mean that the command was completed successfully, only that the reply was unmarshalled. You must also check the **M_Status** within the reply.

15.1.9. SEELib_FreeCommand

```
extern int SEELib_FreeCommand(struct M_Command *cmd);
```

This function frees a command structure and is equivalent to the generic stub function **NFastApp_FreeCommand** (described in the *nCore CodeSafe API Documentation*).

15.1.10. SEELib_FreeReply

```
extern int SEELib_FreeReply(struct M_Reply *reply);
```

This function frees a reply structure and is equivalent to the generic stub function **NFastApp_FreeReply** (described in the *nCore CodeSafe API Documentation*).

15.1.11. SEELib_SetPort

```
extern void SEELib_SetPort(unsigned short port);
```

CodeSafe 5 for nShield 5 only: Sets a custom port to bind to for receiving SEEJobs from the host.

By default, port **8888** is used, and that is also the default port used by client-side configuration support. If using the default port, there is no need to call this function. For a custom port to take effect, this must be called before **SEELib_init()**.

To disable listening for SEEJobs altogether, call **SEELib_SetPort(0)** before **SEELib_init()**.

15.1.12. SEELib_SubmitCoreJob

```
extern int SEELib_SubmitCoreJob( const unsigned char *data, unsigned int len );
```

This function puts a job on the input queue for processing by the core. The byte block is passed in **data** and **len**. It should be a full marshalled **M_Command** with a valid tag at the start.

This function returns an **M_Status**, which is typically **OK** or **BufferFull** (if **len** is too big).

15.1.13. SEELib_GetCoreJob

```
extern int SEELib_GetCoreJob ( unsigned char *buf, M_Word *len_io );
```

This function blocks and waits for a job submitted to the core to be returned. On entry, **buf** points to a buffer of length (***len_io**) **max**. On exit, if successful, ***len_io** is the length of bytes returned.

This function returns an **M_Status**, which is typically **OK** or **BufferFull** (if **len_io** is too big).

15.1.14. SEELib_GetUserDataLen

```
extern M_Word SEELib_GetUserDataLen ( void );
```

In CodeSafe 5, this function gets the length in bytes of the **/etc/userdata.codesafe** file in the filesystem of the container.

If this data has been discarded because **SEELib_ReleaseUserData()** has been called, this function returns **0**.

15.1.15. SEELib_Submit

```
extern int SEELib_Submit(M_Command *cmd, M_Reply *reply, PEVENT ev, SEELib_ContextHandle tctx);
```

This function submits the command specified in `cmd`. The transaction listener thread calls `EventSet ev`, if `ev` is non-NULL, when the reply returns for this command. The reply is unmarshalled into `reply` and `tctx` is returned to the caller in `SEELib_Query`.

Unlike `SEELib_SubmitCoreJob` this function can be called at the same time as another thread is blocking in `SEELib_Transact`.

`SEELib_StartTransactListener` must have been called before this function is called.

15.1.16. SEELib_Query

```
extern int SEELib_Query(M_Reply **replay, SEELib_ContextHandle *tctx_r);
```

This function is called to receive a reply that is being held by the transaction listener thread. It is typically called after having been woken from `EventWait` as a result of the transaction listener thread posting to the event passed in to `SEELib_Submit`.

If `*replay` is NULL, `SEELib_Query` accepts any returned reply, and `*replay` is changed to point to that reply. If `*replay` is not NULL, the function accepts the reply specified; other replies are queued internally.

`tctx_r` can be NULL. If it is not, the `tctx` used when submitting the reply is stored in `*tctx_r`. `SEELib_Query` can return, in addition to the usual return values, `TransactionNotYetComplete` if the reply (or any reply if `*replay` was NULL) has not come back from the core yet.

`SEELib_StartTransactListener` must have been called before this function is called.

15.1.17. SEELib_AwaitJob

```
extern int SEELib_AwaitJob( M_Word *tag_out, unsigned char *buf, M_Word *len_io );
```

This function blocks and waits for the next `SEEJob` to come in from the host-side application. On entry, `*buf` and `*len_io` give the base and length of a buffer area to receive the job. On return, `*len_io` is set to the length delivered (if the job is received successfully). This buffer is a copy of the `seeargs` field of the `SEEJob` that was sent by the host-side application.

The `*tag_out` value is the tag for this command. Each transaction must have a unique tag when sent from the host-side application to ensure transactions are returned to their required caller. The generation of unique tags is handled by the host-side compatibility layer. The tag must be returned in the `SEELib_ReturnJob` so that the host-side compatibility layer associates the reply with this transaction.

The `SEELib_AwaitJob` function returns an `M_Status`, which is `OK` on success and normally, but not always, `BufferFull` on failure.



If you use `SEELib_StartProcessorThreads()`, these function calls are done automatically and you should not call this function yourself.

15.1.18. SEELib_AwaitJobEx

```
extern void SEELib_AwaitJobEx( M_Word *tag_out, unsigned char *buf, M_Word *len_io, unsigned flags );
```

Block on the socket waiting for a `SEEJob` command from the host.

The output parameters are filled with information obtained from the message itself. On entry, `*buf` and `*len_io` give the base and length of a buffer area to receive the job. On return, `*len_io` is set to the length delivered (if the job is received successfully). This buffer is a copy of the `seeargs` field of the `SEEJob` command. The `*tag_out` value is the tag for this command.

15.1.19. SEELib_ReturnJob

```
extern void SEELib_ReturnJob( M_Word tag, const unsigned char *data, unsigned int len );
```

This function returns an `SEEJob` reply to the host-side application. It is sent in a way that the host-side compatibility layer can interpret and write into the corresponding reply struct on the host-side.



If you use the `SEELib_StartProcessorThreads()` function, it calls `SEELib_ReturnJob()` for you.

The tag field must match the tag supplied in the `SEELib_AwaitJob()` call that created the job.

The given data is copied away and forms the `seereply` field of the `SEEJob` reply on the host-side application.

15.1.20. SEELib_StartProcessorThreads

```

struct ProcessThreadCtx; /* User-defined */
typedef struct SEELib_ProcessContext
{
    struct ProcessThreadCtx *uc;

    unsigned char *iobuf;
    int iobuf_maxlen;
}
SEELib_ProcessContext;

typedef struct ProcessThreadCtx * (*SEELib_InitFn) (SEELib_ProcessContext *pC);

/* Function called during thread initialisation */
typedef int (*SEELib_Fn) ( SEELib_ProcessContext *pC, M_Word tag, int in_len );

/* Function to process an SEELib; data is sent in & out via pC->iobuf.
Returns length being returned.
*/
extern int SEELib_StartProcessorThreads(int nthreads, int stacksize, SEELib_InitFn
pfnInit, SEELib_Fn pfnProcess);

```

This function causes the SEE compatibility layer to start a number of processing threads. Each thread has its own **SEELib_ProcessContext** allocated, which remains constant throughout the life of the thread.

A working buffer for a given thread is allocated; the **iobuf** member points to this buffer and **iobuf_maxlen** is set to the size. Data for the **SEELib** is passed in and out through this buffer.

For each thread, the supplied **SEELib_InitFn** is called first, and the **ProcessThreadCtx** pointer it returns is stored in the **SEELib_ProcessContext** structure. This structure is typically a convenient thread-local storage. The pointer may be NULL if it is not required.

When a job arrives for the given thread, the supplied **SEELib_Fn** is called. It is passed the **SEELib_ProcessContext** pointer **pC**, a tag, and a length (**in_len**). The **SEELib** data is at **pC->iobuf**, length **in_len**. The tag is for information only. The function processes the data and leave a reply at **pC->iobuf**. The return value from the function indicates the number of bytes to be returned from this buffer.

15.1.21. SEELib_StartSEELibListener

```
extern int SEELib_StartSEELibListener(PEVENT ev);
```

This function starts the **SEELib** listener thread which blocks calling **SEELib_AwaitJob**, caches the new job and then sets the event **ev** if **ev** is non-NULL.

Use **SEELib_QuerySEELib** to receive any **SEELib**s that have been cached by this listener thread, followed by **SEELib_ReturnJob** to reply to the **SEELib**, then followed by **SEELib_Re-**

lease **SEEJob** to free the buffer.

It is safe to call this function multiple times, however calls after the first call have no effect.

15.1.22. SEELib_QuerySEEJob

```
extern M_Status SEELib_QuerySEEJob( M_Word *tag_out, unsigned char **buf, M_Word *len );
```

This function is called to receive a **SEEJob** that is being held by the **SEEJob** listener thread. It is typically called after having been woken from **EventWait** as a result of the **SEEJob** listener thread setting the event passed in to **SEELib_StartSEEJobListener**.

buf is set to the buffer containing the **SEEJob**, **len** is set to the length of the data contained in **buf**.

This function returns **TransactionNotYetComplete** if there were no outstanding **SEEJobs**.

15.1.23. SEELib_ReleaseSEEJob

```
extern void SEELib_ReleaseSEEJob( unsigned char **buf );
```

This function is called to release a buffer which was returned from **SEELib_QuerySEEJob**. It must be called after the buffer specified by **buf** in a call to **SEELib_QuerySEEJob** has been finished with. This function is safe to call even if ***buf** is NULL. In addition, it sets ***buf** to NULL on completion.

15.2. Host-side SEEJobs

Host-side applications using **SEEJobs** can send them as normal **nCore** commands over a **hardserver** connection, referencing the **SEE World ID** of the **SEE machine** in question. The **hardserver** will automatically dispatch such commands over the mutually authenticated **SSH tunnel** to the **SEE machine** where applicable.

SEEJobs can be sent as **M_Command** commands with the **cmd** set as either **Cmd_SEEJob** (which does not time out, except due to communication failure) and **Cmd_FastSEEJob** (which times out after 2 minutes if the **SEE machine** does not reply to that job in that timeframe, in which case the status is set to **Status_HardwareFailed**, but this is not a fatal error unless the communication as a whole has failed).

Java clients may alternatively use the **seeJob()** helper method of the **PublishedSEEWORLD** or

SEEWor1d5 classes.

16. System calls allowed by CodeSafe 5 SEE machines

SEE machines are restricted to a subset of Linux system calls they can execute.

Attempting to execute any other system call will return **-1** and set **errno** to **ENOSYS**.

Allowed system calls	
1 __NR_exit	2 __NR_fork
3 __NR_read	4 __NR_write
5 __NR_open	6 __NR_close
7 __NR_waitpid	8 __NR_creat
9 __NR_link	10 __NR_unlink
11 __NR_execve	12 __NR_chdir
13 __NR_time	15 __NR_chmod
16 __NR_lchown	19 __NR_lseek
20 __NR_getpid	24 __NR_getuid
27 __NR_alarm	29 __NR_pause
30 __NR_utime	33 __NR_access
34 __NR_nice	36 __NR_sync
37 __NR_kill	38 __NR_rename
39 __NR_mkdir	40 __NR_rmdir
41 __NR_dup	42 __NR_pipe
43 __NR_times	45 __NR_brk
47 __NR_getgid	49 __NR_geteuid
50 __NR_getegid	54 __NR_ioctl
55 __NR_fcntl	57 __NR_setpgid
60 __NR_umask	63 __NR_dup2
64 __NR_getppid	65 __NR_getpgrp
66 __NR_setsid	75 __NR_setrlimit
77 __NR_getrusage	78 __NR_gettimeofday
80 __NR_getgroups	83 __NR_symlink

Allowed system calls	
85 __NR_readlink	88 __NR_reboot
90 __NR_mmap	91 __NR_munmap
92 __NR_truncate	93 __NR_ftruncate
94 __NR_fchmod	95 __NR_fchown
96 __NR_getpriority	97 __NR_setpriority
99 __NR_statfs	100 __NR_fstatfs
102 __NR_socketcall	104 __NR_setitimer
105 __NR_getitimer	106 __NR_stat
107 __NR_lstat	108 __NR_fstat
114 __NR_wait4	117 __NR_ipc
118 __NR_fsync	120 __NR_clone
122 __NR_uname	125 __NR_mprotect
132 __NR_getpgid	133 __NR_fchdir
140 __NR__llseek	141 __NR_getdents
142 __NR__newselect	143 __NR_flock
144 __NR_msync	145 __NR_readv
146 __NR_writev	147 __NR_getsid
148 __NR_fdatasync	158 __NR_sched_yield
162 __NR_nanosleep	163 __NR_mremap
167 __NR_poll	172 __NR_rt_sigreturn
173 __NR_rt_sigaction	174 __NR_rt_sigprocmask
175 __NR_rt_sigpending	176 __NR_rt_sigtimedwait
177 __NR_rt_sigqueueinfo	178 __NR_rt_sigsuspend
179 __NR_pread64	180 __NR_pwrite64
181 __NR_chown	182 __NR_getcwd
185 __NR_sigaltstack	186 __NR_sendfile
190 __NR_ugetrlimit	202 __NR_getdents64
205 __NR_madvise	207 __NR_gettid
208 __NR_tkill	221 __NR_futex

Allowed system calls	
232 __NR_set_tid_address	234 __NR_exit_group
236 __NR_epoll_create	237 __NR_epoll_ctl
238 __NR_epoll_wait	246 __NR_clock_gettime
247 __NR_clock_getres	248 __NR_clock_nanosleep
250 __NR_tgkill	251 __NR_utimes
252 __NR_statfs64	253 __NR_fstatfs64
272 __NR_waitid	280 __NR_pselect6
281 __NR_ppoll	286 __NR_openat
287 __NR_mkdirat	289 __NR_fchownat
291 __NR_newfstatat	292 __NR_unlinkat
293 __NR_renameat	294 __NR_linkat
295 __NR_symlinkat	296 __NR_readlinkat
297 __NR_fchmodat	298 __NR_faccessat
303 __NR_epoll_pwait	304 __NR_utimensat
307 __NR_eventfd	309 __NR_fallocate
315 __NR_epoll_create1	316 __NR_dup3
317 __NR_pipe2	320 __NR_preadv
321 __NR_pwritev	322 __NR_rt_tgsigqueueinfo
325 __NR_prlimit64	326 __NR_socket
327 __NR_bind	328 __NR_connect
329 __NR_listen	330 __NR_accept
331 __NR_getsockname	332 __NR_getpeername
333 __NR_socketpair	334 __NR_send
335 __NR_sendto	336 __NR_recv
337 __NR_recvfrom	338 __NR_shutdown
339 __NR_setsockopt	340 __NR_getsockopt
341 __NR_sendmsg	342 __NR_recvmsg
343 __NR_recvmsg	344 __NR_accept4
348 __NR_syncfs	349 __NR_sendmmsg

Allowed system calls	
357 __NR_renameat2	362 __NR_execveat
365 __NR_membarrier	380 __NR_preadv2
381 __NR_pwritev2	383 __NR_statx



The `getrandom` syscall is not supported in CodeSafe 5 and will set `ENOSYS`. Use either the `Cmd_GenerateRandom` nCore command, or `/dev/random` or `/dev/urandom` within the CodeSafe 5 application in order to obtain HSM RNG instead.